

CCTV

www.securondistributie.nl

Datum: 2/2/2021

Analoge camera's HD/CVBS

[MINI DOME CAMERA](#)

[BULLET CAMERA](#)











[SPEEDDOME](#)











[PTZ SYSTEMEN](#)

[VERBORGEN & MINI CAMERA'S](#)







Analoge camera's HD/CVBS - Mini dome camera

Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-697	HYU-697		4 in 1 dome PRO series with Smart IR of 15~20 m for outdoors. 1/2,9" CMOS, 2MP at 1080P. 4 in 1 video output by DIP switch. 2,8 mm lens. ICR filter. OSD, AWB, AGC, 2D-DNR, BLC, WDR digital. IP65. Lightning-proof. 12V DC.	Prijs op aanvraag
HYU-699	HYU-699		4 in 1 dome PRO series with IR of 15~20 m for outdoors. 1/2,9" CMOS, 2MP at 1080P. 4 in 1 video output switch by DIP switch. 2,8 mm lens. ICR filter. OSD, AWB, AGC, 2D-DNR, BLC, Digital WDR. IP65. Lightning-proof. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-700	HYU-700		4 in 1 dome PRO series with IR illumination of 15~20 m for outdoors. 1/2,9" CMOS, 2MP at 1080P. 4 in 1 video output switch via DIP switch. 2,8 mm lens. ICR filter. OSD, AWB, AGC, 2D-DNR, BLC, digital WDR. IP65. Lightning-proof. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-503	HYU-503		4 in 1 dome PRO series with Smart IR of 20 m for outdoors. 2MP CMOS. 4 in 1 (HDCVI / HDTV / AHD / 960H). 2,8 mm fixed lens (103°). ICR filter. OSD, digital WDR. IP66. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-504	HYU-504		4 in 1 dome PRO series with Smart IR of 20 m, for outdoors. CMOS, 2MP. 4 in 1 (HDCVI / HDTV / AHD / 960H). 2,8 mm fixed lens (103°). ICR filter. OSD, digital WDR. IP66. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-807	HYU-807		Fixed dome 4 in 1 PRO series with 20m Smart IR for indoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). Fixed 2,8 mm (106.4 °) lens. ICR filter. OSD, AWB, AGC, BLC, HLC, digital WDR, 2D-DNR, image adjustments, mirror mode. It incorporates a microphone. Coaxial audio. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-502	HYU-502		4 in 1 dome PRO series with Smart IR of 20 m for outdoors. 2MP CMOS. 4 in 1 (HDCVI / HDTV / AHD / 960H). 2,8 mm fixed lens (103°). ICR. OSD, digital WDR. IP66. 3AXIS. 12V DC.	Prijs op aanvraag

HYU-670	HYU-670		NightFighter 4 in 1 minidome with STARLIGHT technology and Smart IR of 30 m for outdoors. 2MP CMOS. 4 in 1 switch output. 2,8 mm lens (106°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-808	HYU-808		Fixed dome 4 in 1 PRO series with 20m Smart IR for indoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). Fixed 2.8 mm (106.4 °) lens. ICR filter. OSD, AWB, AGC, BLC, HLC, digital WDR, 2D-DNR, image adjustments, mirror mode. It incorporates a microphone. Coaxial audio. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-704	HYU-704		4 in 1 dome PRO series with IR illumination of 20~30 m for outdoors. 1/2,9" CMOS, 2MP at 1080P. 4 in 1 video output via DIP switch. 2,8 mm lens. ICR filter. OSD, AWB, AGC, 2D-DNR, BLC, digital WDR. IP65. Lightning-proof. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-765	HYU-765		4-in-1 HYUNDAI NEXT GEN dome PRO series with 40 m Smart IR for outdoors. 2MP CMOS. 1080P @ 25/30fps. 4-in-1 video output switch. 2.8 mm lens (106.4 °). ICR filter AWB, AGC, BLC, HLC, BLC, digital WDR, 3D-DNR. . IP67 3AXIS. 12V DC	Prijs op aanvraag
HYU-701	HYU-701		4 in 1 dome PRO series with IR illumination of 20~30 m for outdoors. 1/2,9" CMOS, 2MP at 1080P. 4 in 1 video output via DIP switch. 2,8 ~ 12 mm varifocal lens. ICR filter. OSD, AWB, AGC, 2D-DNR, BLC, digital WDR. IP65. Lightning-proof. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-669	HYU-669		NightFighter 4 in 1 minidome with STARLIGHT technology and Smart IR of 30 m, for indoors. 2MP CMOS. 4 in 1 video output switch. 2,8 mm lens (106°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-702	HYU-702		4 in 1 dome PRO series with IR illumination of 20~30 m for outdoors. 1/2,9" CMOS, 2MP at 1080P. 4 in 1 video output via DIP switch. 2,8 ~ 12 mm varifocal lens. ICR filter. OSD, AWB, AGC, 2D-DNR, BLC, WDR digital. IP65. Lightning-proof. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-671	HYU-671		NightFighter 4 in 1 minidome with STARLIGHT technology and Smart IR of 50 m for outdoors. 2MP CMOS. 4 in 1 switch video output. 2,8 mm lens (106°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-765N	HYU-765N		Fixed dome 4 in 1 HYUNDAI NEXT GEN PRO series. Smart IR up to 40 meters. 2 megapixel CMOS. 1080P (1920x1080) resolution at 25 ips. 2.8 mm (106.4 °) fixed lens. Switchable 4-in-1 video output. ICR filter. OSD menu control via coaxial cable (UTC). Digital WDR, 2D-DNR. It incorporates a microphone. Supports coaxial cable audio transmission (only compatible with ZVR HYUNDAI with audio). Metal and plastic housing. Degree of protection IP67. 3AXIS. 12V DC	Prijs op aanvraag
HYU-518	HYU-518		4 in 1 dome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 ~ 12 mm varifocal lens (114,5°~35,1°). ICR filter. OSD, ATW, AGC, BLC, digital WDR, DNR, mirror mode, Anti-flicker, motion detection and privacy mask. IP66. 3AXIS. 12V DC.	Prijs op aanvraag










HYU-703	HYU-703		4 in 1 dome PRO series with IR illumination of 20~30 m for outdoors. 1/2.9" CMOS, 2MP at 1080P. 4 in 1 video output via DIP switch. 2.8 ~ 12 mm varifocal lens. ICR filter. OSD, AWB, AGC, 2D-DNR, BLC, digital WDR. IP65. Lightning-proof. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-512	HYU-512		4 in 1 fixed dome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2.8 ~ 12 mm varifocal lens (102,25°~32°). ICR. OSD, ATW/MWB, AGC, BLC, Digital WDR. IP66. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-506	HYU-506		4 in 1 dome PRO series with Smart IR of 20 m for outdoors. CMOS, 2MP. 4 in 1 (HDCVI / HDTV / AHD / 960H). 2.8 mm fixed lens (103°). ICR filter. OSD, digital WDR. IP66. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-507	HYU-507		HDTV dome PRO series with Smart IR of 40 m for outdoors. 3MP CMOS. HD-TVI video output. 2.8 mm (84°) fixed lens. ICR filter. OSD, ATW/MWB, AGC, BLC, digital WDR. IP66. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-566	HYU-566		HD-TVI dome PIR series with Smart IR of 20 m and motion detection by active PIR, for outdoors. 2MP CMOS. HD-TVI video output. 2.8 mm lens (103°). 0,01 lux color. ICR. OSD, ATW, AGC, BLC, DNR, mirror and image adjustment. Visual alarm via white led. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-809	HYU-809		4 in 1 HYUNDAI NEXT GEN dome PRO series with Smart IR of 30 m for outdoors. 2MP CMOS. 1080P resolution @ 25/30fps 4-in-1 video output switch. 2.8 mm lens (106.4 °). ICR filter. AWB, AGC, BLC, HLC, digital WDR, 2D-DNR. It incorporates microphone. Supports coaxial audio. IP67 3AXIS. 12V DC	Prijs op aanvraag
HYU-389	HYU-389		HD-TVI fixed dome PRO series with Smart IR of 20 m for outdoors. 2MP CMOS. HD-TVI video output. 2.8 mm fixed lens (103°). ICR filter. ATW, AGC, DNR. IP66. 3AXIS. 12V DC. PoC compatible	Prijs op aanvraag
HYU-487	HYU-487		4 in 1 dome PRO series with Smart IR of 20 m for indoors. 5MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2.8 mm fixed lens (85,5°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, brightness, sharpness, mirror. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-487N	HYU-487N		4 in 1 dome PRO series with Smart IR of 20 m for indoors. 5MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2.8 mm fixed lens (85°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, brightness, sharpness, mirror. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-482	HYU-482		HD-TVI fixed dome PIR series with Smart IR of 20 m and motion detection by active PIR, for outdoors. 2MP CMOS. HD-TVI video output. 2.8 mm fixed lens (103,5°). 0,005 lux. ICR filter. OSD, ATW, MWB, AGC, BLC, real WDR 120dB, 3D-DNR, mirror, motion detection and privacy mask. Visual alarm by white led. IP67. 3AXIS. 12V DC.	Prijs op aanvraag










NEW

HYU-515	HYU-515		4 in 1 dome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 ~ 12 mm varifocal lens (102,25°-32°). ICR filter. OSD, ATW/MWB, AGC, BLC, digital WDR. IP66. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-516	HYU-516		4 in 1 dome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 ~ 12 mm varifocal lens (102,25°-32°). ICR filter. OSD, ATW/MWB, AGC, BLC, digital WDR. IP66. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-812	HYU-812		4 in 1 fixed dome HYUNDAI NEXT GEN PRO series with 20m Smart IR for indoors. 5MP CMOS. 5MP @ 20ips resolution Switchable 4-in-1 video output. 2.8mm (85.5 °) fixed lens. ICR filter. AWB, AGC, BLC, HLC, Digital WDR, 2D-DNR. It incorporates a microphone. Coaxial audio. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-246	HYU-246		4 in 1 PRO series with IR illumination of 30 meters, for outdoors. 1/3" CMOS, 3 MP. 4 in 1 output via DIP switch (HDCVI @1080P / HDTV @3MP / AHD @3MP / CVBS @960H). ICR filter. 2.7~13 mm varifocal lens. OSD, AWB, MWB, AGC, AES, 2D-DNR, BLC, digital WDR. IP66. 12V DC	Prijs op aanvraag
HYU-695	HYU-695		4 in 1 dome StarLight series with IR illumination of 20~30 m for outdoors. 1/2,8" Sony CMOS, 2MP at 1080P. 4 in 1 video output switch. 2.8~12 mm motor lens with autofocus. ICR filter. OSD, AWB, AGC, 2D/3D-DNR, BLC, digital WDR, sense up, defog, mirror, motion detection and privacy mask. IP66. Lightning-proof. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-675	HYU-675		NightFighter 4 in 1 minidome with STARLIGHT technology and Smart IR of 30 m , vandal protection for outdoors. 2MP CMOS. 4 in 1 video output switch . 2.8 mm (106°) lens. ICR. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment. IP67, IK10. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-486	HYU-486		4 in 1 vandal dome PRO series with Smart IR of 20 m, for outdoors. CMOS, 5MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2.8 mm (85,5°) fixed lens. ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, brightness, sharpness, mirror. IP67, IK10. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-486N	HYU-486		4 in 1 HYUNDAI Next Gen fixed dome with 20 m Smart IR vandal resistant for outdoor use. 5MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2.8 mm fixed lens. ICR filter. OSD, ATW, AGC, BLC, HLC, digital WDR, 2D-DNR, image adjustments, mirror mode. IP67, IK10. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-814	HYU-814		4 in 1 fixed dome HYUNDAI NEXT GEN PRO series with 30m Smart IR for outdoor. 5MP CMOS. 5MP @ 20ips resolution Switchable 4-in-1 video output. 2.8mm (85.5 °) fixed lens. ICR filter. AWB, AGC, BLC, HLC, Digital WDR, 2D-DNR. It incorporates a microphone. Supports coaxial audio. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-576	HYU-576		4 in 1 dome PRO series with Smart IR of 20 m for outdoors. 5MP CMOS. 4 in 1 (HDCVI / HDTV / AHD / 960H). 2,8 mm (85,5°) fixed lens. ICR. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, brightness, sharpness, mirror. IP67. 3AXIS. 12V DC.	Prijs op aanvraag

HYU-813	HYU-813		4 in 1 fixed dome HYUNDAI NEXT GEN PRO series with 30m Smart IR for outdoor. 5MP CMOS. 5MP @ 20ips resolution Switchable 4-in-1 video output. 2.8mm (85.5 °) fixed lens. ICR filter. AWB, AGC, BLC, HLC, Digital WDR, 2D-DNR. It incorporates a microphone. Coaxial audio. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-777	HYU-777		4-in-1 HYUNDAI NEXT GEN dome PRO series with Smart IR of 20 m for outdoors. 2MP CMOS. 1080P @ 25/30fps 4 in 1 video output switch. 2.8 mm (106 °) lens. ICR filter AWB, AGC, BLC, HLC, digital WDR, 2D-DNR. It incorporates PIR detector, strobe and siren. IP67 3AXIS. 12V DC	Prijs op aanvraag
HYU-672	HYU-672		NightFighter 4 in 1 dome with STARLIGHT technology and Smart IR of 70 m for outdoors. 2MP CMOS. 4 in 1 switch video output. 2.7 ~ 13,5 mm motor lens (102°~31°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-696	HYU-696		4 in 1 dome StarLight series with IR illumination of 20~30 m for outdoors. 1/2,8" Sony CMOS, 2MP at 1080P. 4 in 1 video output switch. 2,8~12 mm motor lens with autofocus. ICR filter. OSD, AWB, AGC, 2D/3D-DNR, BLC, digital WDR, sense up, defog, mirror, motion detection and privacy mask. IP66. Lightning-proof. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-570	HYU-570		HD-TVI dome PRO series with Smart IR of 20 m for outdoors. 5MP CMOS. HD-TVI video output. 2,8 mm lens (85,5°). ICR. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, image adjustment. IP67. 3AXIS. 12V DC. Compatible with PoC.af.	Prijs op aanvraag
HYU-57N	HYU-57N		4 in 1 dome StarLight series for outdoors. 1/2,8" Sony CMOS, 2,1MP at 1080P. 4 in 1 output (HDCVI / HDTV1 / AHD / 960H). 2,7~13,5 mm StarLight varifocal lens. OSD, AWB, ATW, AGC, BLC, digital WDR, 2D/3D-DNR, defog, mirror, motion detection and privacy mask. IP65, Lightning-proof. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-509	HYU-509		HDTV1 dome StarLight with Smart IR of 40 m for outdoors. 2MP CMOS. HDTV1 video output. 2,8 ~ 12 mm (103°~32,1°) motor lens with autofocus. ICR filter. OSD, ATW/MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, mirror mode, sharpness and brightness adjustment, motino detection and privacy mask. IP67. 3AXIS. 12V DC	Prijs op aanvraag
HYU-759	HYU-759		NightFighter 4 in 1 dome with STARLIGHT technology and Smart IR of 70 m for outdoors. 2MP CMOS. 4 in 1 switch video output. 2,7 ~ 13,5 mm motor lens (102°~31°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-390	HYU-390		HD-TVI fixed dome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. HD-TVI video output. 2,7 ~ 12 mm varifocal lens (102,25°~32°). ICR. ATW, AGC, DNR. IP66. 3AXIS. 12V DC. PoC compatible .	Prijs op aanvraag
HYU-547	HYU-547		HD-TVI StarLight with Smart IR of 20 m, for indoors. 2MP CMOS. HDTV1 video output. 2,8 ~ 12 mm motorized lens (103°~32,1°). ICR filter. OSD, ATW, AGC, BLC, WDR 120 dB, 3D-DNR, brightness, sharpness, mirror, motion detection and privacy mask. IP50. 3AXIS. 12V DC.	Prijs op aanvraag











NEW











HYU-804	HYU-804		4-in-1 fixed dome Color View series with 20 m white lighting for outdoor use. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2.8 mm (104 °) fixed lens. 24 hour color mode (does not switch to B / W). OSD, ATW, AGC, BLC, HLC, 120dB real WDR, 3D-DNR, saturation settings, video sensor and privacy masks. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-891	HYU-891		4-in-1 fixed dome Color View series with 40 m white lighting for outdoor use. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2.8 mm fixed lens. 24 hour color mode (does not switch to B / W). OSD, ATW, AGC, BLC, HLC, HLS, WDR 130dB, 2D / 3D-DNR, image adjustments, mirror mode, video sensor and privacy masks. IP68. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-548	HYU-548		HDTV dome Starlight with Smart IR of 40 m for outdoors. 2MP CMOS. HDTV output. 2.8 ~ 12 mm (103°-32,1°) motorized lens with autofocus. ICR. OSD, ATW/MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, mirror mode, brightness and sharpness adjustment, motion detection and privacy mask. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-589	HYU-589		4 in 1 dome PRO series with Smart IR of 30 m for outdoor. CMOS of 8,3MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 mm lens (102,2°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, DNR, brightness, sharpness, mirror. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-604	HYU-604		4 in 1 vandal dome PRO series with Smart IR of 60 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,7~13,5 mm motorized varifocal lens (103°-32,1°). AGC, AWB, motion detection and privacy mask. Real WDR 120 dB , 3D-DNR, brightness, sharpness, mirror. IP67. IK10 3AXIS. 12V DC.	Prijs op aanvraag
HYU-573	HYU-573		HDTV dome Starlight with Smart IR of 40 m, for outdoors. 2MP CMOS. HDTV output. 2,8~12 mm (103°-32,1°) motorized lens with autofocus. ICR. OSD, ATW/MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, mirror mode, brightness and sharpness adjustment, motion detection and privacy mask. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-588	HYU-588		4 in 1 dome PRO series with Smart IR of 30 m,vandal proof for outdoors. 8,3MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 mm lens (102,2°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, DNR, brightness, sharpness, mirror. IP67, IK10. 3AXIS. 12V DC	Prijs op aanvraag
HYU-438	HYU-438		HD-TVI TURBO HD 4.0 fixed dome ULTRAPRO series with IR illumination of 60 m, for outdoors. 8,3MP CMOS. Double video output HD-TVI/CVBS. 2.8 mm fixed lens (102.2°). ICR filter. OSD, ATW, MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, defog, mirror, privacy mask. IP67. 3AXIS. 12V DC	Prijs op aanvraag
HYU-490	HYU-490		4 in 1 vandal dome PRO series with Smart IR of 60 m, for outdoors. 5MP CMOS. 4 in 1 (HDCVI/HDTV/AHD/960H). 2,7 ~ 13,5 mm (95,7°-29,1°) motorized lens with manual focus. ICR. 0,01 lux. OSD, AWB, AGC, BLC, digital WDR, DNR, brightness, sharpness, mirror. IP67, IK10. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-572	HYU-572		HD-TVI dome PRO series with Smart IR of 40 m for outdoors. 5MP CMOS. HD-TVI video output. 2,7~13,5 mm motorized lens (95,7°-29,1°). ICR. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, image adjustment. IP67. 3AXIS. 12V DC. PoC.at compatible.	Prijs op aanvraag











HYU-775	HYU-775		4 in 1 HYUNDAI NEXT GEN dome ULTRAPRO series with Smart Light of 20 m for outdoors. 2MP CMOS. 1080P resolution @ 25 / 30ips Switchable 4-in-1 video output. 2.8 mm lens. ICR filter AWB, AGC, BLC, HLC, HLS, WDR 130dB, 2D / 3D-DNR, Anti flicker, motion detection and privacy masks. It incorporates PIR detector, strobe and siren. 1 alarm output IP67 3AXIS. 12V DC	Prijs op aanvraag
HYU-802	HYU-802		4-in-1 fixed dome Color View series with 20 m white lighting for outdoor use. 5MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2.8 mm fixed lens. 24 hour color mode (does not switch to B / W). OSD, ATW, AGC, BLC, HLC, 130dB real WDR, 3D-DNR, image adjustments, mirror mode, video sensor and privacy masks. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-657	HYU-657		HD-TVI minidome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. HD-TVI video output. 2.8~12 mm motor lens with autofocus (103°~32,1°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment, motion detection and privacy mask. IP67. 3AXIS. 12V DC. PoC.at compatible.	Prijs op aanvraag
HYU-757	HYU-757		4 in 1 HYUNDAI NEXT GEN dome PRO series with 60 m Smart IR for outdoors. 5MP CMOS. 5MP @ 20fps 4-in-1 video output switch. 2.7 ~ 13.5 mm motor lens with autofocus (92.3 ° ~ 29.3 °). ICR filter AWB, AGC, BLC, WDR 130dB, 3D-DNR, motion detection and privacy masks. IP67 3AXIS. 12V DC, 24V AC.	Prijs op aanvraag
HYU-758	HYU-758		4 in 1 HYUNDAI NEXT GEN dome PRO series with 60 m Smart IR for outdoors. 5MP CMOS. 5MP@20fps 4-in-1 video output switch. 2.7 ~ 13.5 mm (92.3 ° ~ 29.3 °) motor lens with autofocus. ICR filter AWB, AGC, BLC, WDR 130dB, 3D-DNR, video sensor and privacy masks. IP67 3AXIS. 12V DC, 24V AC.	Prijs op aanvraag
HYU-658	HYU-658		HD-TVI dome PRO series with Smart IR of 60 m, vandal protection for outdoors. 2MP CMOS. HD-TVI video output. 2.7~13.5 mm motorlens with autofocus (103°~32,1°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 130dB, 3D-DNR, image adjustment, motion detection and privacy mask. IP67, IK10. 3AXIS. 12V DC. PoC.af compatible.	Prijs op aanvraag
HYU-591	HYU-591		4 in 1 dome ULTRAPRO series with Smart IR of 60 m for outdoors. 8,3MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,7 ~ 13,5 mm motor lens with autofocus (108,1°~45,6°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, DNR, brightness, sharpness, mirror. IP67. 3AXIS. 9V~15V DC	Prijs op aanvraag
HYU-592	HYU-592		4 in 1 dome ULTRAPRO series with Smart IR of 60 m for outdoors. 8,3MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,7 ~ 13,5 mm motorized lens with autofocus (108,1°~45,6°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, DNR, brightness, sharpness, mirror. IP67. 3AXIS. 9V~15V DC.	Prijs op aanvraag
HYU-436	HYU-436		HD-TVI TURBO HD 4.0 fixed dome ULTRAPRO series with IR illumination of 80 m for outdoors. 8,3MP CMOS. Double video output HD-TVI/CVBS. 2,8~12 mm motorized lens (108,1°~45,6°) with autofocus. ICR. OSD, ATW, MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, defog, mirror, privacy mask. IP67. 3AXIS. 12V DC.	Prijs op aanvraag

Analoge camera's HD/CVBS - Bullet camera











Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
------------	---------	------------	--------------	-----------








HYU-510	HYU-510		4 in 1 bullet camera LITE series with Smart IR of 20 m for outdoors. 1MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2.8 mm (92°) fixed lens. ICR. IP66. 3AXIS. 12V DC	Prijs op aanvraag
HYU-698	HYU-698		4 in 1 bullet camera PRO series with IR illumination of 20~30 m for outdoors. 1/2,9" Aptina CMOS, 2MP at 1080P. 4 in 1 video output switch via DIP switch. 2.8 mm lens. ICR filter. OSD, AWB, AGC, 2D/3D-DNR, BLC, Digital WDR, sense up, defog, mirror, motion detection and privacy mask. IP66. Lightning-proof. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-761	HYU-761		4 in 1 HYUNDAI NEXT GEN bullet camera LITE series with Smart IR of 20 m, for outdoors. 2MP CMOS. 4 in 1 video output switch. 2.8 mm (103 °) lens. ICR filter IP66 3AXIS. 12V DC	Prijs op aanvraag
HYU-146	HYU-146		4 in 1 bullet camera PRO series with IR illumination of 20m, for outdoors. 1/3" Sony Exmor CMOS, 2MP@1080p 4 in 1 output (HDCVI/HDTV/AHD/960H). 2.8 mm fixed lens (90°). ICR filter. OSD, AWB, AGC, BLC, HLC, digital WDR. IP66. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-673	HYU-673		NightFighter 4 in 1 bullet camera with STARLIGHT technology and Smart IR of 30 m for outdoors. 2MP CMOS. 4 in 1 video output switch. 2.8 mm lens (106°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-511	HYU-511		4 in 1 bullet camera PRO series with Smart IR of 20 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2.8 mm fixed lens (103°). ICR filter. OSD, ATW/MWB, AGC, BLC, digital WDR. IP66. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-337	HYU-337		4 in 1 bullet camera PRO series with IR illumination up to 30 meters, for outdoors. 1/2,9" Sony CMOS, 2,1 MP @ 1080P. 4 in 1 output (HDCVI / HDTV / AHD / 960H). ICR filter. 2.8 mm fixed lens. OSD, AWB, AGC, AES, 2D/3D-DNR, BLC, HLC, digital WDR, Sense Up, defog, motion detection and privacy mask. IP66. Lightning-proof. Soporte 3AXIS. 12V DC	Prijs op aanvraag
HYU-387	HYU-387		HD-TVI bullet camera PRO series with Smart IR of 20 meters, for outdoors. 2MP CMOS. HD-TVI video output. 2.8 mm fixed lens (103°). ICR filter. ATW, AGC, DNR. IP66. 3AXIS bracket. 12V DC. PoC compatible.	Prijs op aanvraag
HYU-513	HYU-513		4 in 1 bullet camera PRO series with Smart IR of 20 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2.8 mm fixed lens (103°). ICR filter. OSD, digital WDR. IP66. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-806	HYU-806		4 in 1 bullet camera PRO series with Smart IR of 30 m for outdoor. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2.8 mm (106.4 °) fixed lens. ICR filter. OSD, AWB, AGC, BLC, HLC, digital WDR, 2D-DNR, image adjustments, mirror mode. It incorporates a microphone. Coaxial audio. IP67. 3AXIS. 12V DC.	Prijs op aanvraag

HYU-705	HYU-705		4 in 1 bullet camera PRO series with Smart IR of 30~40 m for outdoors. 1/2,9" Sony CMOS, 2MP at 1080P. 4 in 1 video output via DIP switch. 2,8 ~ 12 mm varifocal lens. ICR filter. OSD, AWB, AGC, 2D/3D-DNR, BLC, digital WDR, sense up, defog, mirror, motion detection and privacy mask. IP66. Lightning-proof. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-567	HYU-567		HD-TVI bullet camera PIR series with Smart IR of 20 m and motion detection by active PIR. 5MP CMOS. HD-TVI video output. 2,8 mm lens (85,5°). 0,01 lux color. ICR. OSD, ATW, AGC, BLC, DNR, mirror and image adjustment. Visual alarm via white led. IP67. 3AXIS bracket. 12V DC.	Prijs op aanvraag
HYU-565	HYU-565		HD-TVI bullet camera PIR series with Smart IR of 20 m and motion detection by active PIR, for outdoors, 2MP CMOS. HD-TVI video output. 2,8 mm lens (103°). 0,01 lux color. ICR. OSD, ATW, AGC, BLC, DNR, mirror and image adjustment. Visual alarm via white led. IP67. 3AXIS bracket. 12V DC.	Prijs op aanvraag
HYU-150N	HYU-150N		4 in 1 bullet camera LITE series with IR of 40 m, for outdoors. 1/4" CMOS, 1MP @ 720P. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8~12 mm varifocal lens. ICR filter. IP66. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-249	HYU-249		4 in 1 bullet camera serie PRO series with IR illumination of 40 m, for outdoors. 1/3" Sony CMOS , 2,4MP @ 1080P. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 mm fixed lens. ICR filter. OSD, AWB, AGC, BLC, HLC, 2D/3D-DNR. IP66. 3AXIS brakcet. 12V DC.	Prijs op aanvraag
HYU-481	HYU-481		HD-TVI bullet camera PIR series with Smart IR of 20 m and motion detection by active PIR, for outdoors. 2MP CMOS. HD-TVI video output. 2,8 mm fixed lens (103,5°). 0,005 lux. ICR filter. OSD, ATW, MWB, AGC, BLC, real WDR 120dB, 3D-DNR, mirror, motion detection and privacy mask. Visual alarm by white led. IP67. 3AXIS bracket. 12V DC.	Prijs op aanvraag
HYU-244	HYU-244		4 in 1 bullet camera PRO series with IR illuminatino of 40 meters, for outdoors. 1/3" CMOS, 3 MP. 4 in 1 output via DIP switch (HDCVI @1080P / HDTV @3MP / AHD @3MP / CVBS @960H). ICR. 2,8 ~ 12 mm varifocal lens. OSD, AWB, MWB, AGC, AES, 2D-DNR, BLC, WDR real. IP66. 3AXIS bracket. 12V DC.	Prijs op aanvraag
HYU-811	HYU-811		4 in 1 HYUNDAI NEXT GEN bullet camera PRO series with Smart IR of 30 m for outdoors. 5MP CMOS. 5MP@20fps. 4 in 1 video output switch. 2,8 mm (85,5°) lens. ICR filter. AWB, AGC, BLC, HLC, WDR digital, 2D-DNR. Microphone incorporated. Audio via coaxial. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-517	HYU-517		4 in 1 bullet camera PRO series with Smart IR of 40 m, for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 ~ 12 mm varifocal lens (102,25°~32°). ICR filter. OSD, ATW/MWB, AGC, BLC, digital WDR. IP66. 3AXIS bracket. 12V DC	Prijs op aanvraag
HYU-340N	HYU-340N		4 in 1 bullet camera PRO series with IR illumination of 40 m, for outdoorsr. 1/2,9" Sony® CMOS, 5 MP. 4 in 1 output DIP switch (HDCVI @4MP / HDTV @5MP / AHD @5MP / CVBS @960H). ICR filter. 2,8 mm fixed lens. OSD, WB, AE, DNR, mirror. IP66. 3AXIS bracket. 12V DC.	Prijs op aanvraag



HYU-165N	HYU-165N		4 in 1 bullet camera PRO series with IR illumination of 50 meters, for outdoors. 1/2.9" Sony CMOS. 2MP @ 1080p. 4 in 1 output with DIP switch (HDCVI / HDTV / AHD / 960H). Black tempered glass. 2.7~13.5 mm motorized lens with improved autofocus (synchronous focus). ICR. OSD, AWB, AGC, AES, ATR, 2D-NR, digital WDR. IP66. 3AXIS bracket. 12V DC	Prijs op aanvraag
HYU-250	HYU-250		4 in 1 bullet camera PRO series with IR illumination of 40 m, for outdoors. 1/3" Panasonic CMOS, 2,1MP @ 1080P. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8~12 mm motorized lens. ICR filter. OSD, AWB, AGC, BLC, HLC, real WDR 120 dB, 2D/3D-DNR, defog, mirror, motion detection and privacy mask. IP66. 3AXIS. 12V DC	Prijs op aanvraag
HYU-694	HYU-694		4 in 1 bullet camera StarLight series with IR illumination of 30~40 m for outdoors. 1/2,8" Sony CMOS, 2MP at 1080P. 4 in 1 video output switch. 2,8~12 mm motor lens with autofocus. ICR filter. OSD, AWB, AGC, 2D/3D-DNR, BLC, digital WDR, sense up, defog, mirror, motion detection and privacy mask. IP66. Lightning-proof. 3AXIS. 12V DC	Prijs op aanvraag
HYU-569	HYU-569		HD-TVI bullet camera PRO series with Smart IR of 20 m for outdoors. 5MP CMOS. HD-TVI video output. 2.8 mm lens (85,5°). ICR. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, image adjustment. IP67. 3AXIS bracket. 12V DC. PoC.af. compatible	Prijs op aanvraag
HYU-335	HYU-335		4 in 1 bullet camera PRO series with IR illumination of 40 meters, for outdoors. 1/2,9" Sony CMOS, 2 MP @ 1080P. 4 in 1 output (HDCVI / HDTV / AHD / 960H). ICR filter. 2.8 ~ 12 mm varifocal lens. OSD, AWB, AGC, AES, 2D/3D-DNR, BLC, digital WDR, Sense Up, defog, motion detection and privacy mask. IP66. Lightning-proof. 3AXIS bracket. 12V DC. □	Prijs op aanvraag
HYU-776	HYU-776		4 in 1 bullet camera HYUNDAI NEXT GEN PRO series with Smart IR of 40 m for outdoor. 2MP CMOS. 1080P @ 25 / 30ips resolution Switchable 4-in-1 video output. 2.8 mm (106 °) fixed lens. ICR filter. AWB, AGC, BLC, HLC, digital WDR, 2D-DNR. It incorporates PIR detector, strobe light and siren. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-55N	HYU-55N		4 in 1 dome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 ~ 12 mm varifocal lens (102,25°~32°). ICR filter. OSD, ATW/MWB, AGC, BLC, digital WDR. IP66. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-471	HYU-471		4 in 1 bullet camera PRO series with IR illumination up to 40 meters for outdoors. 1/2,5" CMOS, 5 MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H). ICR. 0,02 lux. 3,3~12 mm varifocal lens. OSD, AWB, AGC, BLC, HLC, digital WDR, 2D/3D-DNR, defog, mirror, motion detection. IP66. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-805	HYU-805		4 in 1 bullet camera Color View series with 20 m white lighting for outdoor. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2.8 mm fixed lens. 24 hour color mode (does not switch to B / W). OSD, ATW, AGC, BLC, HLC, 130dB real WDR, 3D-DNR, image adjustments, mirror mode, video sensor and privacy masks. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-890	HYU-890		4 in 1 bullet camera Color View series with 20 m white lighting for outdoor. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2.8 mm fixed lens. 24 hour color mode (does not switch to B / W). OSD, ATW, AGC, BLC, HLC, HLS, WDR 130dB, 2D / 3D-DNR, image adjustments, mirror mode, video sensor and privacy masks. IP68. 3AXIS. 12V DC.	Prijs op aanvraag

NEW

HYU-508	HYU-508		HD-TVI TURBO HD StarLight bullet camera with Smart IR of 40 m for outdoors. 2MP CMOS. HDTV video output. 2,8 ~ 12 mm (103°~32,1°) motorized lens with autofocus. ICR filter. OSD, ATW/MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, mirror mode, brightness and sharpness adjustment, motion detection and privacy mask. IP67. 3AXIS bracket. 12V DC.	Prijs op aanvraag
HYU-674	HYU-674		NightFighter 4 in 1 bullet camera with STARLIGHT technology and Smart IR of 70 m for outdoors. 2MP CMOS. 4 in 1 video output switch. 2,7 ~ 13,5 mm motorized lens (102°~31°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-762	HYU-762		NightFighter 4 in 1 bullet camera with STARLIGHT technology and Smart IR of 70 m for outdoors. 2MP CMOS. 4 in 1 video output switch. 2,7 ~ 13,5 mm motorized lens (102°~31°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-585	HYU-585		4 in 1 bullet camera Color View series with white illumination of 20 meters for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 3,6 mm lens (83,6°). 24 hour color mode (no switch to B/W). OSD, ATW/MWB, AGC, BLC, real WDR 120dB, 3D-DNR, image adjustment, mirror mode, motion detection and privacy mask. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-388	HYU-388		HD-TVI bullet camera PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. HD-TVI video output. 2,7 ~ 12 mm varifocal lens (102,5°~32°). ICR filter. ATW, AGC, DNR. IP66. 3AXIS bracket. 12V DC. PoC compatible.	Prijs op aanvraag
HYU-587	HYU-587		4 in 1 bullet camera PRO series with Smart IR of 30 m for outdoors. 8,3MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 mm lens (102,2°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, DNR, brightness, sharpness, mirror. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-489	HYU-489		4 in 1 bullet camera PRO series with Smart IR of 40 m for outdoors. 5MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,7 ~ 13,5 mm motorized lens (95,7°~29,1°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, brightness, sharpness, mirror. IP67. 3AXIS. DC12V.	Prijs op aanvraag
HYU-763	HYU-763		4-in-1 HYUNDAI NEXT GEN bullet camera PRO series with Smart IR of 80 m, for outdoors. 5MP CMOS. 5MP @ 20fps 4-in-1 video output switch. 2,7 ~ 13,5 mm motor lens with autofocus (92,3 ° ~ 29,3 °). ICR filter AWB, AGC, BLC, WDR 130dB, 3D-DNR, motion detection and privacy masks. IP67 3AXIS. 12V DC, 24V AC.	Prijs op aanvraag
HYU-803	HYU-803		4 in 1 bullet camera Color View series with 20 m white lighting for outdoor. 5MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 mm fixed lens. 24 hour color mode (does not switch to B / W). OSD, ATW, AGC, BLC, HLC, 130dB real WDR, 3D-DNR, image adjustments, mirror mode, video sensor and privacy masks. IP67. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-437	HYU-437		HD-TVI TURBO HD 4.0 bullet camera ULTRAPRO series with IR illumination of 40 m for outdoors. 8,3MP CMOS. Double video output HD-TVI/CVBS. 2,8 mm fixed lens (102,2°). ICR filter. OSD, ATW, MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, defog, mirror, privacy mask. IP67. 3AXIS bracket. 12V DC.	Prijs op aanvraag





HYU-655	HYU-655		4 in 1 bullet camera PRO series with IR up to 40 m for outdoors. 1/2,8" Sony® CMOS, 5 MP. 4 in 1 output switch (HDCVI @4MP / HDTVI @5MP / AHD @5MP / CVBS @960H). UTC supported. ICR filter. 2,7 ~ 13,5 mm motor lens with autofocus. OSD, ATW/MWB, BLC, digital WDR , 2D/3D-DNR. IP67. 3AXIS. 12V DC	Prijs op aanvraag
HYU-656	HYU-656		HD-TVI bullet camera PRO series with Smart IR of 80 m for outdoors. 2MP CMOS. Video output HD-TVI. 2,7~13,5 mm motor lens with autofocus (103°~32,1°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 130dB, 3D-DNR, image adjustment, motion detection and privacy mask. IP67. 3AXIS. 12V DC. PoC.at compatible.	Prijs op aanvraag
HYU-571	HYU-571		HD-TVI bullet camera PRO series with Smart IR of 40 m for outdoors. 5MP CMOS. HD-TVI video output. 2,7~13,5 mm motorized lens (95,7°~29,1°). ICR. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, image adjustment. IP67. 3AXIS bracket. 12V DC. PoC.at compatible.	Prijs op aanvraag
HYU-399	HYU-399		4 in 1 bullet camera PRO series with IR illumination of 60~80 m, for outdoors. 1/2,9" Sony CMOS, 2MP @ 1080P. 4 in 1 output (switch via OSD): CVBS output + triple output: CVI, TVI, AHD. 5~50 mm motorized lens. ICR filter. OSD, AWB, AGC, 2D/3D-DNR, BLC, digital WDR, sense up, defog, mirror, motion detection and privacy mask. IP66. Lightning-proof. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-590	HYU-590		4 in 1 bullet camera ULTRAPRO series with Smart IR of 80 m for outdoors. 8,3MP CMOS. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). 2,7 ~ 13,5 mm motor lens with autofocus (108,1°~45,6°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, DNR, brightness, sharpness, mirror. IP67. 3AXIS. 9V~15V DC.	Prijs op aanvraag
HYU-541	HYU-541		4 in 1 bullet camera PRO series with IR of 60~80 m for outdoors. 1/2,7" CMOS, 5 MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). ICR filter. 0,01 lux. 5~50 mm motorized lens with autofocus. OSD, AWB, ATW, AGC, BLC, digital WDR, 2D/3D-NR, defog, mirror, motion detection and privacy mask. IP66. 3AXIS bracket. 12V DC.	Prijs op aanvraag
HYU-530	HYU-530		HD-TVI Starlight bullet camera with Smart IR of 110 m for outdoors. CMOS, 2MP. Dual video output HD-TVI/CVBS. 5~50 mm (59,8°~6,2°) motorized lens with autofocus. 62X digital zoom. ICR. OSD, ATW, AGC, BLC, real WDR 120dB, 3D-DNR, defog, mirror, motion detection and privacy mask. IP66. Calefactor. 3AXIS bracket. 24V AC / 12V DC.	Prijs op aanvraag

Analoge camera's HD/CVBS - Speeddome


Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-456	HYU-456		4 in 1 PTZ dome PRO series of 180°/sec. with IR of 100 m for outdoors. 1/2,9" Sony CMOS, 2MP at 1080P. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). 10X optical zoom 5,1~51 mm (54°~4,9°). ICR filter. 0,05/0,01 lux. OSD, AWB, AGC, BLC, digital WDR, 2D/3D-DNR, mirror, flip, defog. 256 presets. RS485. IP66. Lightning-proof. 12V DC. 4".	Prijs op aanvraag
HYU-689	HYU-689		4 in 1 PTZ of 80°/sec. with IR illumination of 100 m, for outdoors. 1/2,8" CMOS, 2 MP. 1080P at 25 fps. 15X optical zoom 5~75 mm (53,8°~4°). 16X digital zoom. 4 in 1 output (HDCVI / HDTVI / AHD / CVBS). ICR filter. OSD, AWB, AGC, BLC, HLC, EIS, WDR true 120 dB, 3D-DNR, privacy mask. 256 presets. Pelco-D/P. RS485 Half Duplex. IP66, Lightning-proof. 12V DC. Wall bracket and power supply included.	Prijs op aanvraag

HYU-430N	HYU-430N		4 in 1 motorized dome of 80°/sec. with IR illumination of 100 m, for outdoors. 1/2,8" CMOS, 2 MP. 1080P at 25 fps. 25X optical zoom of 4,8~120 mm (57,6°~2,5°). 16X digital zoom. 4 in 1 output (HDCVI / HDTV / AHD / CVBS). ICR. OSD, AWB, AGC, BLC, HLC, EIS, WDR true 120 dB, 3D-DNR, privacy mask. 256 presets. Pelco-D/P. RS485 Half Duplex. IP66, Lightning-proof. 12V DC. Wall mount and power supply included.	Prijs op aanvraag
HYU-82	HYU-82		HDTV motorized dome (350°/sec) with IR illumination of 150 m, for outdoors. 1/3" Sony CMOS, 2MP @ 1080p. HDTV output 5~100 mm with 20X optical zoom. ICR. OSD, AWB, AGC. 80 presets. IP66. Lens cleaner. Lightning-proof. Stand included. 12V DC (included)	Prijs op aanvraag
HYU-431N	HYU-431N		4 in 1 PTZ PRO series of 120°/sec. with IR illumination of 150 m, for outdoors. 1/2,8" CMOS, 2MP. 4 in 1 output (HDTV / HDCVI / AHD / 960H). 25X optical zoom of 4,8~120 mm (57,6°~2,5°). 16X digital zoom. ICR filter. OSD, AWB, AGC, BLC, WDR true 120dB, 3D-DNR, EIS, 8 privacy mask. 256 presets. Pelco-D/P. RS485 Half Duplex. 2 input / 1 output of alarm. IP66, Lightning-proof. 24V AC. Bracket and power supply is not included.	Prijs op aanvraag
HYU-692	HYU-692		4 in 1 PTZ of 160°/sec. with IR illumination of 150 m, for outdoors. 1/2,8" CMOS, 2 MP. 1080P at 25 fps. 32X optical zoom of 4,8~153 mm (54,2°~1,97°). 16X digital zoom. 4 in 1 output (HDCVI / HDTV / AHD / CVBS). ICR filter. OSD, AWB, AGC, BLC, HLC, EIS, WDR true 120 dB, 3D-DNR, privacy mask. 256 presets. Pelco-D/P. RS485 Half Duplex. IP66, Lightning-proof. 24V AC. Bracket and power supply is not included.	Prijs op aanvraag

Analoge camera's HD/CVBS - PTZ systemen

Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-454	HYU-454		4 in 1 PTZ bullet camera PRO series with IR of 30~40 m for outdoors. 1/2,7 CMOS, 2 MP. 1080P resolution. 4 in 1 output (HDCVI / HDTV / AHD / 960H) by DIP switch. ICR filter. 0,1/0,01 lux. 4X optical zoom (2,8~12 mm). OSD, AWB, AGC, 2D/3D-DNR, mirror. 180° positioner. 1 preset. IP65. 12V DC.	Prijs op aanvraag
HYU-454N	HYU-454N		4-in-1 PTZ bullet camera PRO series with 20 ~ 25m IR illumination for outdoor. 1 / 2.9 Sony® Exmor 2.1 megapixel CMOS. 1080P resolution. 4 in 1 output (HDCVI / HDTV / AHD / 960H) switchable by DIP switch. ICR filter. 0.01 lux. 4X optical zoom (2.8 ~ 12mm) with autofocus. OSD, AWB, AGC, WDR digital, 2D / 3D-DNR, defog, mirror, video sensor and privacy mask. 250 ° positioner. 1 preset. IP66, Lightning-proof 6KV. 12V DC.	Prijs op aanvraag
HYU-113N	HYU-113N		HD-TVI bullet PTZ camera PRO series with IR illumination of 50 m, for outdoors. 1/2,8" Sony CMOS, 2MP @ 1080P. 4 in 1 output (HDCVI / HDTV / AHD / 960H) switch by RS485 (Pelco-D). 2,8~12 mm motorized lens. ICR dual filter. OSD, BLC, real WDR, ROI. 250° positioner. 255 presets. Pelco, RS485. IP66. Lightning-proof. 12V DC	Prijs op aanvraag
HYU-112N	HYU-112N		PTZ bullet camera CVI/TVI/AHD LITE series with IR illumination of 80 m, for outdoors. 1/2,9" Sony CMOS, 2MP @ 1080P. BNC output (CVI/TVI/AHD). 5,1~51 mm motorized lens, fixed iris. ICR filter. OSD, AWB, AGC, 2D/3D-NR, mirror mode, privacy mask. 250° positioner. 255 presets. IP66. 12V DC.	Prijs op aanvraag

Analoge camera's HD/CVBS - Verborgen & mini camera's










Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-483	HYU-483		HD-TVI compact camera PIR series with Smart IR of 20 m and motion detection by active PIR, for indoors. 2MP CMOS. HD-TVI video output. 2,8 mm fixed lens (103,5°). 0,005 lux. ICR filter. OSD, ATW, MWB, AGC, BLC, real WDR 120dB, 3D-DNR, mirror, motion detection and privacy mask. 2 way audio (built in microphone). 12V DC	Prijs op aanvraag











Analoge recorders HD/CVBS











ANALOGUE RECORDERS











ANALOGUE RECORDERS INCL. HDD

Analoge recorders HD/CVBS - analoge recorders

Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-234	ZVR4104P-2MLITE		4 channel 5 in 1 ZVR (HDCVI/HDTV/AHD/CVBS + 1 IP channel). H.264+/H.264. G.711u audio format. 2 way audio. 4 ch@720p. Recording: 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF, full 720p. HDMI and VGA output @ 1080p. 1HDD SATA. Onvif, P2P, DDNS, 2USB, 12VDC	Prijs op aanvraag
HYU-778	ZVR4104P-2MLITE-AUDIO		ZVR 5 in 1 with 4 channels HDCVI / HDTV / AHD / CVBS + 1 channel IP 1080P. Video format H.264 + / H264. Two-way audio. Play 4ch 720P. 1080N, 720P, WD1, D1, VGA, CIF, QVGA, QCIF recording. Simultaneous HDMI and VGA outputs at 1080P. 1 SATA HDD capacity. RJ45 Fast Ethernet. Onvif, P2P, DDNS. 2 USB. 12V DC.	Prijs op aanvraag
HYU-781	ZVR4104M-A-2MLITE-AUDIO		ZVR 5 in 1 with 4 channels HDCVI / HDTV / AHD / CVBS + 1 channel IP 1080P. Video format H.264 + / H264. Two-way audio. Coaxial audio. Simultaneous 4-channel playback. 1080N, 720P, WD1, D1, VGA, CIF, QVGA, QCIF recording. Simultaneous HDMI and VGA outputs at 1080P. Capacity of 1 HDD SATA up to 6TB. RJ45 Fast Ethernet. Onvif, P2P, DDNS. 2 USB. 12V DC.	Prijs op aanvraag
HYU-370	ZVR5104M-4MLITE		4 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 1 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 4 channel playback at 1080P. Recording: 4M-N, 3MP (channel1, 15 fps, only TVI), 4MP (1 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.	Prijs op aanvraag
HYU-787	HYU-787		ZVR 5 in 1 with 4 channels HDCVI / HDTV / AHD / CVBS + 1 channel IP 6MP. Video format H.265 Pro / H.265 Pro / H.265 / H.264 + / H.264. Two-way audio. 4-channel synchronized playback. Recording 4M-N, 3MP, 1080P, 1080P Lite, 720P, 720P Lite, WD1, 4CIF, VGA, CIF. HDMI and VGA outputs at 1080P. Behavioral analysis and facial detection. 1 HDD SATA capacity up to 10TB. RJ45 Fast Ethernet. Onvif, P2P, DDNS. RS485. 2 USB2.0. 12V DC.	Prijs op aanvraag
HYU-383	ZVR5104P-4MLITE		4 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 1 IP channels. H.265+/H265/H.264+/H264. 2 way audio. 4 channel playback 1080P. Recording 4 MP (1 IP input) 4M-N, 3MP (channel 1, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF (25 fps). HDMI and VGA at 1080P. 1 HDD SATA capacity. Onvif, P2P, DDNS. 2 USB. 12V DC	Prijs op aanvraag
HYU-790	ZVR5104M-4MLITE-AUDIO		4 channel 5 in 1 HYUNDAI ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. 2 way audio. 4 channel Synchronous playback. Recording: 4MP, 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). Salidas HDMI (4K) and VGA (1080P) simultaneous. BNC output at D1/4CIF. 1 HDD SATA capacity. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.	Prijs op aanvraag
HYU-784	ZVR5104P-4MLITE-AUDIO		4 channel 5 in 1 HYUNDAI ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. 2 way audio. Synchronous playback of 4 channels. 4MP, 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 ips). HDMI (4K) and VGA (1080P) simultaneous output. BNC output at D1/4CIF. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.	Prijs op aanvraag
HYU-779	ZVR4108P-2MLITE-AUDIO		8 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channels 1080P. H.264+/H264. 2 way audio. 8 channel playback at 720P. Recording: 1080N, 720P, WD1, D1, VGA, CIF, QVGA, QCIF. HDMI and VGA simultaneous output at 1080P. 1 HDD SATA. RJ45 Fast Ethernet. Onvif, P2P, DDNS. 2 USB. 12V DC.	Prijs op aanvraag





HYU-793	ZVR5104M-A-4MLITE-AUDIO		4 channel 5 in 1 HYUNDAI ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channel. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. 2 way audio. Alarm: 4 in / 8 out. 4 channel synchronous playback. Recording 4MP, 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI (4K) and VGA (1080P) simultaneous output. BNC output at D1/4CIF. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.	Prijs op aanvraag
HYU-373	ZVR5104M-A-4MLITE		4 channel 5 in 1 ZVR, HDCVI/HDTV/AHD/CVBS + 1 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 4 channel playback at 1080P. Recording: 4M-N, 3MP (channel 1, 15 fps, only TVI), 4MP (1 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. Alarm: 4 in / 1 out. 1 HDD SATA capacity. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.	Prijs op aanvraag
HYU-782	ZVR4108M-A-2MLITE-AUDIO		ZVR 5 in 1 with 8 channels HDCVI / HDTV / AHD / CVBS + 2 channels IP 5MP. Video format H.264 + / H264. Two-way audio. Coaxial audio. 8 channel simultaneous playback. 1080N, 720P, WD1, D1, VGA, CIF, QVGA, QCIF recording. Simultaneous HDMI and VGA outputs at 1080P. Capacity of 1 HDD SATA up to 6TB. RJ45 Fast Ethernet. Onvif, P2P, DDNS. 2 USB. 12V DC.	Prijs op aanvraag
HYU-371	ZVR5108M-4MLITE		8 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 8 channel playback at 1080P. Recording: 4M-N, 3MP (channel1 & 2, 15 fps, only TVI), 4MP (2 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.	Prijs op aanvraag
HYU-788	HYU-788		ZVR 5 in 1 with 8 channels HDCVI / HDTV / AHD / CVBS + 2 channels IP 6MP. Video format H.265 Pro / H.265 Pro / H.265 / H.264 + / H.264. Two-way audio. 8-channel synchronized playback. Recording 4M-N, 3MP, 1080P, 1080P Lite, 720P, 720P Lite, WD1, 4CIF, VGA, CIF. HDMI and VGA outputs at 1080P. Behavioral analysis and facial detection. 1 HDD SATA capacity up to 10TB. RJ45 Fast Ethernet. Onvif, P2P, DDNS. RS485, 2 USB2.0. 12V DC.	Prijs op aanvraag
HYU-580	AI-ZVR5104M-4MLITE		4 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. 2 way audio. 4 channel simultaneous playback. Recording: 6MP (only IP), 4M-N, 3MP (channel 1, 15 fps, only TVI/AHD), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI and VGA simultaneous output at 1080P. BNC output at D1/4CIF. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.	Prijs op aanvraag
HYU-391N	ZVR5104M-POC		4 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 1 IP channels. H.265+/H265/H.264+/H264. 2 way audio. 4 channel playback 1080P. Recording 3MP (channels 1 to 4, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA at 1080P. 1 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. DC48V. Compatible with PoC cameras.	Prijs op aanvraag
HYU-384N	ZVR5108P-4M-A-LITE		Dahua PTZ IP dome StarLight AI series of 200°/sec. with IR lighting of 100 m, for outdoor. Supports 4G H.265 + / H.265 / H.264 + / H.264 / MJPEG format. 1/2.8" Sony® STARVIS™ CMOS 4 MP. Triple stream. Resolution up to 4MP @ 25ips. 25X optical zoom of 4.8 ~ 120 mm. 16X digital zoom ICR filter 0.005 / 0.0005 lux. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 2D / 3D-DNR, digital defog, EIS, motion detection, privacy masks, Perimeter protection, video metadata, facial detection.	Prijs op aanvraag
HYU-236	ZVR4116P-2MLITE		16 channel 5 in 1 ZVR (HDCVI/HDTV/AHD/CVBS + 2 IP channel). H.264+/H.264. G.711u audio format. 2 way audio. 16 ch@720p. Recording: 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF, full 720p lite. HDMI and VGA output @ 1080p. 1HDD SATA. Onvif, P2P, DDNS, 2USB, 12VDC	Prijs op aanvraag
HYU-780	ZVR4116P-2MLITE-AUDIO		ZVR 5 in 1 of 16 channels HDCVI / HDTV / AHD / CVBS + 2 channels IP 5MP. Video format H.265 + / H.265 / H.264 + / H264. Two-way audio. Coaxial audio. 16-channel simultaneous playback. 1080N, 720P, WD1, D1, VGA, CIF, QVGA, QCIF recording. Simultaneous HDMI and VGA outputs at 1080P. 1 HDD SATA capacity up to 10TB. RJ45 Fast Ethernet. Onvif, P2P, DDNS. 2 USB. 12V DC.	Prijs op aanvraag

HYU-799	ZVR7104-A-5M-AUDIO		4 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 4 IP ch. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. Audio: 1 in / 1 out. Alarm: 4 in / 1 out. 4 channel synchronous playback. Recording: 8M-N (8 fps, only TVI/IP), 5MP (12 fps, only TVI/AHD), 4MP (15 fps), 3MP (18 fps), 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI (4K, 2K) and VGA (1080P) simultaneous output. BNC output at D1/4CIF. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485, 12V DC.	Prijs op aanvraag
HYU-796	AI-ZVR7104-5M-AUDIO		4 channel 5 in 1 HYUNDAI ZVR AiSense series of HDCVI / HDTV / AHD / CVBS + 2 IP channels. Video formats H.265 Pro +, H265 Pro, H.265, H.264 +, H.264. Bidirectional audio. 4 CH synchronized playback. Recording 8MP (8 fps, TVI / IP only), 5MP (12 fps), 4MP (15 fps), 3MP (18 fps), 1080P, 720P, 960H, D1 / 4CIF, VGA, CIF, QVGA, QCIF (25 fps). Simultaneous HDMI (2K) and VGA (1080P) outputs. BNC output to D1 / 4CIF. Capacity of 1 SATA HDD. Onvif, P2P.	Prijs op aanvraag
HYU-783	ZVR4116M-A-2MLITE-AUDIO		ZVR 5 in 1 of 16 channels HDCVI / HDTV / AHD / CVBS + 2 channels IP 5MP. Video format H.265 + / H.265 / H.264 + / H264. Two-way audio. Coaxial audio. 16-channel simultaneous playback. 1080N, 720P, WD1, D1, VGA, CIF, QVGA, QCIF recording. Simultaneous HDMI and VGA outputs at 1080P. 1 HDD SATA capacity up to 10TB. RJ45 Fast Ethernet. Onvif, P2P, DDNS. 2 USB. 12V DC.	Prijs op aanvraag
HYU-562	ZVR7104-A-POC		4 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channel. H.265+/H265/H.264+/H264. Audio: 4 input / 1 output. 4 channel simultaneous playback. Recording: 6MP (IP), 5MP (TVI, AHD), 4MP, 1080P, 720P, WD1, 4CIF, VGA, CIF. BNC output at 4CIF. HDMI and VGA at 1080P. Alarm: 4 input / 1 output. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 48V DC. Compatible with PoC up to 5MP	Prijs op aanvraag
HYU-372	ZVR5116M-4MLITE		16 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 16 channel playback at 1080P. Recording: 4M-N, 3MP (channels 1 to 4, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI output at 4K and VGA at 1080P. 1 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485, 12V DC.	Prijs op aanvraag
HYU-581	AI-ZVR5108M-4MLITE		8 ch 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 4 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. 2 way audio. 8 channel simultaneous playback. Recording: 6MP (only IP), 4M-N, 3MP (channels 1 and 2, 15 fps, only TVI/AHD), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI and VGA simultaneous output at 1080P. BNC output at D1/4CIF. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485, 12V DC.	Prijs op aanvraag
HYU-583	AI-ZVR7104-5M		4 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 4 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. Audio: 4 in / 1 out. 4 channel synchronized playback. Recording: 8MP (only IP), 5MP (12 fps, only TVI/AHD), 4MP (15 fps), 3MP (18 fps), 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI and VGA simultaneous output at 1080P. BNC output at D1/4CIF. Alarm: 4 in / 1 out. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485, 12V DC.	Prijs op aanvraag
HYU-800	ZVR7208-A-4KLITE-AUDIO		8 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 8 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. Audio: 1 in / 1 out. Alarm: 8 in / 1 out. Synchronous playback of 8 channels. 8M-N (8 fps, only TVI/IP), 5MP (12 fps, only TVI/AHD), 4MP (15 fps), 3MP (18 fps), 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI (4K, 2K) and VGA (1080P) simultaneous output. BNC output at D1/4CIF. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485, 12V DC.	Prijs op aanvraag
HYU-379	ZVR8104-A-4K		4 channel 5 in 1 TURBO HD 4.0 ZVR, 8MP (10FPS) / 5MP (20FPS) / 4MP (25FPS) / 3MP (18FPS) / 1080P (25FPS) HDCVI/HDTV/AHD/CVBS + 2 IP channels at 8MP. H.265+/H.265/H.264+/H264. Audio: 4 in / 1 out (2 way audio). Recording 8MP/5MP/4MP/3MP (TVI), 1080P/720P (CVI, AHD), WD1/4CIF/VGA/CIF (CVBS), full 4MP in all cameras. BNC a@ 4CIF output. HDMI (4K, 2K) and VGA (1080P) output. 1 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 1 USB.	Prijs op aanvraag
HYU-789	HYU-789		ZVR 5 in 1 of 16 channels HDCVI / HDTV / AHD / CVBS + 2 channels IP 6MP. Video format H.265 Pro / H.265 Pro / H.265 / H.264 + / H.264. Two-way audio. 16-channel synchronized playback. Recording 4M-N, 3MP, 1080P, 1080P Lite, 720P, 720P Lite, WD1, 4CIF, VGA, CIF. Behavioral analysis and facial detection. HDMI and VGA outputs at 1080P. 1 HDD SATA capacity up to 10TB. Gigabit RJ45. Onvif, P2P, DDNS. RS485, USB2.0 + USB3.0, 12V DC.	Prijs op aanvraag

HYU-786	ZVR5116P-4MLITE-AUDIO		16 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 8 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. 2 way audio. Synchronous playback of 16 channels. Recording: 4MP, 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI (4K) and VGA (1080P) simultaneous output. BNC output at D1/4CIF. 1 HDD SATA capacity. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.	Prijs op aanvraag
HYU-385	ZVR5116P-4MLITE		16 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channels. H.265+/H265/H.264+/H264. 2 way audio. 16 channel playback. Recording: 4MP (2 IP inputs), 4M-N, 3MP (channel 1 to 4, 15 fps, only TVI), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF (25 fps). HDMI and VGA output at 1080P. 1 HDD SATA capacity. Onvif, P2P, DDNS. 2 USB. 12V DC.	Prijs op aanvraag
HYU-797	AI-ZVR7108-5M-AUDIO		ZVR 5 in 1 HYUNDAI AiSense series of 8 channels HDCVI / HDTV / AHD / CVBS + 4 IP channels. Video formats H.265 Pro +, H265 Pro, H.265, H.264 +, H.264. Bidirectional audio. 8-channel synchronized playback. Recording 8MP (8 fps, TVI / IP only), 5MP (12 fps), 4MP (15 fps), 3MP (18 fps), 1080P, 720P, 960H, D1 / 4CIF, VGA, CIF, QVGA, QCIF (25 fps), Simultaneous HDMI (2K, 4K) and VGA (1080P) outputs. BNC output to D1 / 4CIF. Capacity of 1 SATA HDD. Onvif, P2P.	Prijs op aanvraag
HYU-375	ZVR5116M-A-4MLITE		16 channel ZVR 5 in 1 HDCVI/HDTV/AHD/CVBS + 2 IP channels. H.265+/H265/H.264+/H264. 2 way audio. 16 channel playback at 1080P. Recording 4M-N, 3MP (channel 1 to 4, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI output at 4K and VGA output at 1080P. Alarm: 16 in / 1 out. 1 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.	Prijs op aanvraag
HYU-795	ZVR5116M-A-4MLITE-AUDIO		16 channel 5 in 1 HYUNDAI ZVR HDCVI/HDTV/AHD/CVBS + 8 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. 2 way audio. Alarm: 4 in / 8 out. 16 channel synchronous playback. Recording: 4MP, 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI (4K) and VGA (1080P) simultaneous output. BNC output at D1/4CIF. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.	Prijs op aanvraag
HYU-584	AI-ZVR7108-4KLITE		8 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 8 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. Audio: 4 in / 1 out. Synchronized playback of 8 channels. Recording: 8MP (8 fps, only TVI/IP), 5MP (12 fps, only TVI/AHD), 4MP (15 fps), 3MP (18 fps), 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI (4K, 2K) and VGA (1080P) simultaneous. BNC output at D1/4CIF. Alarm: 8 in / 4 out. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485.	Prijs op aanvraag
HYU-764	ZVR7116-A-4KLITE		16 ch 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 16 IP ch. Video formats H.265 Pro +, H265 Pro, H.265, H.264 +, H.264. Audio: 4 in / 1 out. Synchronized playback of 16 channels. Recording 8M-N (8 fps, only TVI / IP), 5MP (12 fps, only TVI / AHD), 4MP (15 fps), 3MP (18 fps), 1080P, 720P, 960H, D1 / 4CIF, VGA, CIF , QVGA, QCIF (25 fps). Simultaneous HDMI (4K, 2K) and VGA (1080P) outputs. BNC output to D1 / 4CIF. Capacity of 1 SATA HDD. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC	Prijs op aanvraag
HYU-563	ZVR7208-A-POC		8 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 4 IP channels. H.265+/H265/H.264+/H264. Audio: 4 in / 1 out. 8 channel simultaneous playback. Recording: 8MP (IP), 6MP (TVI, AHD), 4MP, 1080P, 720P, WD1, 4CIF, VGA, CIF. BNC output at 4CIF. HDMI and VGA output at 1080P. Alarm: 8 in / 4 out. 2 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 48V DC. PoC up to 5MP.	Prijs op aanvraag
HYU-582	AI-ZVR5116M-4MLITE		16 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 8 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. 2 way audio. Simultaneous playback of 8 channels. Recording: 6MP (only IP), 4M-N, 3MP (channels 1, 2, 3 and 4, 15 fps, only TVI/AHD), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI and VGA simultaneous output at 1080P. BNC output at D1/4CIF. 1 HDD SATA. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.	Prijs op aanvraag
HYU-231	ZVR7216-A-3M		16 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channels 4MP. H.264+/H264. Audio: 4 in / 1 out (2 way audio). Resolution per channel: 3 Mpx (12FPS) or 1080p, 1080P/Lite/720P (25FPS), BNC output at D1/4CIF. HDMI and VGA output at 1080P. Alarm: 16 in / 4 out. 2 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 1 USB 2.0, 1 USB 3.0, 1 RS485. 12V DC	Prijs op aanvraag

HYU-380	ZVR8208-A-4K		8 channel 5 in 1 TURBO HD 4.0 ZVR 8MP (10FPS) / 5MP (20FPS) / 4MP (25FPS) / 3MP (18FPS) / 1080P (25FPS) HDCVI/HDTV/AHD/CVBS + 2 IP channel up to 8MP. H.265+/H.265/H.264+/H.264. Audio: 8 in / 1 out (2 way audio). Recording: 8MP/5MP/4MP/3MP (TVI), 1080P/720P (CVI, AHD), WD1/4CIF/VGA/CIF (CVBS), full 4MP in all cameras. BNC output @ 4CIF. HDMI (4K, 2K) and VGA (1080P) output. Alarm: 8 in / 1 out. 2 HDD SATA capacity. RJ45 Gigabit. Onvif.	Prijs op aanvraag
HYU-393	ZVR5216M-POC		16 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channels. H.265+/H.265/H.264+/H.264. 2 way audio. 16 channel playback 1080P. Recording 3MP (channels 1 to 4, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI output at 4K and VGA at 1080P. 2 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. DC48V. Compatible with PoC cameras.	Prijs op aanvraag
HYU-801	ZVR7216-A-4KLITE-AUDIO		ZVR 5 in 1 of 16 channels HDCVI / HDTV / AHD / CVBS + 16 channels IP 8MP. Video format H.265 + / H.265 / H.264 + / H.264. 4 audio inputs / 1 output. Coaxial audio. 16-channel simultaneous playback. 8MP, 5MP, 4MP, 3MP, 1080P, 720P, WD1, 4CIF, VGA, CIF recording. Simultaneous HDMI (4K) and VGA (1080P) outputs. 2 HDD SATA capacity up to 10TB. 16 alarm inputs / 4 outputs. Gigabit RJ45. Onvif, P2P, DDNS. RS485, USB2.0 + USB3.0. 12V DC.	Prijs op aanvraag
HYU-564	ZVR7216-A-POC		16 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 8 IP channels. H.265+/H.265/H.264+/H.264. Audio: 4 in / 1 out. 16 channel simultaneous playback. Recording: 8MP (TVI), 6MP (IP), 5MP (TVI, AHD), 4MP, 1080P, 720P, WD1, 4CIF, VGA, CIF. Salida BNC a 4CIF. HDMI (4K, 2K) and VGA (1080P). Alarm: 4 in / 1 out. 2 HDD SATA. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. 220V AC. PoC up to 5MP.	Prijs op aanvraag
HYU-446	ZVR5432-A-4MLITE		32 channels 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 8 IP channels 6MP. H.265+/H.265/H.264+/H.264. Audio: 4 in / 1 out (2 way audio). Recording 6MP (IP), 4M-N (TVI, AHD, 15 fps), 3MP (channels 1 to 4, 15 fps, only TVI), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output (4CIF). BNC output at D1/4CIF. HDMI (4K, 2K) and VGA (1080P) output. Alarm: 16 in / 4 out. 4 HDD SATA capacity. 1 eSATA. RJ45 Gigabit. Onvif. DDNS. 3 USB.	Prijs op aanvraag

Analoge recorders HD/CVBS - Analoge recorders incl. HDD

Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-370-1TB	ZVR5104M-4MLITE-1TB		4 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 1 IP channel. H.265+/H.265/H.264+/H.264. 2 way audio. 4 channel playback at 1080P. Recording: 4M-N, 3MP (channel1, 15 fps, only TVI), 4MP (1 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. Special CCTV HDD of 1 TB. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.	Prijs op aanvraag
HYU-373-1TB	ZVR5104M-A-4MLITE-1TB		4 channel 5 in 1 ZVR, HDCVI/HDTV/AHD/CVBS + 1 IP channel. H.265+/H.265/H.264+/H.264. 2 way audio. 4 channel playback at 1080P. Recording: 4M-N, 3MP (channel 1, 15 fps, only TVI), 4MP (1 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. Alarm: 4 in / 1 out. Special CCTV HDD of 1 TB. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.	Prijs op aanvraag
HYU-371-1TB	ZVR5108M-4MLITE-1TB		8 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channel. H.265+/H.265/H.264+/H.264. 2 way audio. 8 channel playback at 1080P. Recording: 4M-N, 3MP (channel1 & 2, 15 fps, only TVI), 4MP (2 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. Special CCTV HDD of 1 TB. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.	Prijs op aanvraag
HYU-372-2TB	ZVR5116M-4MLITE-2TB		16 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channel. H.265+/H.265/H.264+/H.264. 2 way audio. 16 channel playback at 1080P. Recording: 4M-N, 3MP (channels 1 to 4, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI output at 4K and VGA at 1080P. Special CCTV HDD of 2 TB. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.	Prijs op aanvraag

Netwerk camera's

[MINI DOME CAMERA](#)

[BULLET](#)

[SPEEDDOME](#)

[FISHEYE & PANORAMISCHE CAMERA'S](#)











[VERBORGEN & MINI CAMERA'S](#)



[KENTEKENHERKENNING](#)











[MENSEN TELLEN](#)







Netwerk camera's - Mini dome camera

Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-416N	HYU-416N		IP dome with IR illumination of 30m, for outdoors, 2 MP. H.265+, H.265, H.264+, H.264. 1/2.8" CMOS, 2MP. 1080P, 1.3MP, 720P, etc. Mechanical filter. 0.01 lux. 2.8 mm fixed lens (95°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, ROI. IP67, IK10. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-770	HYU-770		IP HYUNDAI NEXT GEN IP dome Performance Line with IR of 30m for outdoors, 2 MP. H.265 / H.264 / MJPEG format. 1/2.8" CMOS, 2MP. Digital resolution 1080P @ 25FPS. Mechanical filter. 0.028 lux. 2.8 mm lens (114°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy masks, fixed ROI zone, IP67, IK10, 3AXIS, 12V DC, PoE.	Prijs op aanvraag
HYU-415	HYU-415		IP vandal dome with IR illumination of 30m, for outdoors, 2 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2.8" CMOS, 2MP. Digital resolution 1080P, 1.3MP, 720P, etc. Mechanical filter. 0.01 lux. 2.8 mm fixed lens (114°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67. 2AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-769	HYU-769		HYUNDAI NEXT GEN IP vandal dome Performance Line with IR of 30m, for outdoors. 2 MP. H.265 / H.264 / MJPEG. 1/2.8" CMOS, 2MP. Digital resolution 1080P @ 25FPS. Mechanical filter. 0.028 lux. 2.8 mm lens (114°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy masks, fixed ROI zone, IP67, IK10, 2AXIS, 12V DC, PoE.	Prijs op aanvraag
HYU-410N	HYU-410N		IP dome with IR illumination of 30 meters, for outdoors, 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0.01 lux. 2.8 mm fixed lens (100°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67, IK10. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-753	HYU-753		IP dome with IR illumination of 30 meters, for outdoors, 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0.01 lux. 2.8 mm fixed lens (100°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-302N	HYU-302N		Fixed IP dome with IR of 40 m, for outdoors. H.265/H.264. 1/2.9" Sony® CMOS, 2 MP. 2MP @25/30 fps. Dual stream. 2.7 ~ 13.5 mm motorized lens with autofocus. ICR filter. OSD, Digital WDR. Audio: 1 in/out. Onvif. IP66. Reset button. Waterproof cable. 12V DC. PoE.	Prijs op aanvraag
HYU-409	HYU-409		IP vandal dome with IR illumination of 30m, for outdoors, 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution: 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0.01 lux. 2.8 mm fixed lens (100°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67, IK10. 2AXIS. Reset button. 12V DC. PoE.	Prijs op aanvraag

HYU-649	HYU-649		WiFi IP dome with IR of 30m, for outdoors , 2 MP. H.265+/H.265/H.264+/H.264//MJPEG. 1/2,8" CMOS, 2MP. Dual Stream. Mechanical filter. 0,028 lux,2,8 mm lens (114°). OSD, AGC, 3D-DNR, BLC, digital WDR, privacy mask, ROI. Microphone incorporated. MicroSD/SDHC/SDXC. IP66. 2AXIS. 12V DC.	Prijs op aanvraag
HYU-257	HYU-257		Fixed IP dome with IR illumination of 30 m, for outdoors. H.265+/H.264. 1/3" CMOS 4 MP. 4MP @12/15 fps. 2,8 ~ 12 mm autofocus motorized lens. ICR. OSD, WDR, 2 way audio, 3D-NR, motion detection and privacy mask. Waterproof cable, reset button. Onvif. IP66. 12V DC. PoE	Prijs op aanvraag
HYU-664	HYU-664		WiFi IP dome with IR illumination of 30m, for outdoors, 4 MP. H.265+/H.265/H.264+/H.264//MJPEG. 1/3" CMOS, 4MP. Dual stream. Mechanical filter. 0,028 lux. 2.8 mm lens (100°). OSD, AGC, 3D-DNR, BLC, digital WDR, privacy mask, ROI. Microphone incorporated. MicroSD/SDHC/SDXC. IP66. 2AXIS. 12V DC.	Prijs op aanvraag
HYU-617	HYU-617		IP dome, 5MP with IR of 30m, suitable for outdoors. H.265+/H.265/H.264+/H.264//MJPEG. 1/2,7" CMOS, 5MP. 5MP@12,5FPS. ICR filter. 0,028 lux. 2,8 mm lens (100°). OSD, AGC, BLC, Real WDR 120dB, 3D-DNR, motion detection, privacy mask, 1 fixed ROI. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-413	HYU-413		IP vandal dome with IR of 30m, for outdoors, 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8~12 mm (98°~30°) motor lens with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. MicroSD/SDHC/SDXC. IP67, IK10. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-616	HYU-616		IP dome, 5MP with IR of 30m, suitable for outdoors. H.265+/H.265/H.264+/H.264//MJPEG. 1/2,7" CMOS, 5MP. 5MP@12,5FPS. ICR filter. 0,028 lux. 2,8 mm lens (100°). OSD, AGC, BLC, Real WDR 120dB, 3D-DNR, motion detection, privacy mask, 1 fixed ROI. Onvif, ISAPI. IP67. 2AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-741	HYU-741		HYUNDAI NEXTGEN IP dome of 2MP with IR of 30m, vandal proof for outdoors. H.265 + / H.265 / H.264 + / H.264 / MJPEG format. Triple stream. 1/2.8" CMOS 2MP. Digital resolution 1080P @ 25 fps. ICR filter. 0.028 lux. 2.8 mm lens (114 °). OSD, AGC, BLC, HLC, real WDR 120dB, 3D- DNR, 1 fixed ROI zone, IVS, facial detection, reset button, MicroSD, Onvif, ISAPI, IP67, IK10, 3AXIS, 12V DC, PoE.	Prijs op aanvraag
HYU-772	HYU-772		IP HYUNDAI NEXT GEN vandal dome Performance Line with IR of 30m, for outdoors. 2 MP. H.265 + / H.265 / H.264 + / H.264 / MJPEG format. 1/2.8" CMOS, 2MP. Digital resolution 1080P @ 25FPS. Mechanical filter. 0.028 lux. 2.8 ~ 12 mm motor lens (99.6 ° ~ 35 °). OSD, AGC, BLC, WDR 120dB , 3D-DNR, motion detection, privacy masks, fixed ROI zone Intelligent analysis IP67, IK10, 3AXIS, 12V DC, PoE.	Prijs op aanvraag
HYU-773	HYU-773		IP HYUNDAI NEXT GEN dome Performance Line with IR of 30m, for outdoor. 4 MP. H.265 + / H.265 / H.264 + / H.264 / MJPEG format. 1/3 " CMOS, 4MP. Digital resolution of 4MP @ 20FPS. Mechanical filter. 0.02 lux. 2.8 ~ 12 mm motor lens (92.8 ° ~ 29 °). OSD, AGC, BLC, WDR 120dB , 3D-DNR, motion detection, privacy masks, fixed ROI zone , IP67,IK10 3AXIS, 12V DC, PoE.	Prijs op aanvraag
HYU-418	HYU-418		IP dome with IR of 20~30m, for outdoors of 2 MP. H.265+/H.265/H.264+/H.264//MJPEG. 1/2,8" CMOS, 2MP. Digital resolution: 1080P, 1,3MP, 720P, etc. Mechanical filter. 0,01 lux. 2,8~12 mm (90°~35°) motor lens with autofocus. OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag











HYU-742	HYU-742		HYUNDAI NEXTGEN IP dome of 4MP with IR of 30m, vandal proof suitable for outdoors. H.265 + / H.265 / H.264 + / H.264 / MJPEG format. Triple stream. CMOS 1/3 "of 4MP. Digital resolution of 4MP @ 25 fps. ICR filter. 0.018 lux. Fixed optics of 2.8 mm (103 °). OSD, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, 1 fixed ROI zone IVS Facial detection Reset button MicroSD Onvif, ISAPI IP67, IK10 3AXIS 12V DC PoE.	Prijs op aanvraag
HYU-767	HYU-767		HYUNDAI IP dome with IR of 30m , 4MP for outdoors. H.265 / H.264 / MJPEG format. 1/3" CMOS, 4MP. Digital resolution of 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0.018 lux. 2.8 ~ 12 mm (98 ° ~ 28 °) motor lens with autofocus. OSD, AGC, BLC, WDR true 120dB, 3D-DNR, motion detection, privacy masks, fixed ROI zone, MicroSD / SDHC / SDXC slot, IP67, IK10, 3AXIS, 12V DC, PoE.	Prijs op aanvraag
HYU-766	HYU-766		IP dome with IR illumination of 20~30m, for outdoors 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0.01 lux. 2.8~12 mm (98°~30°) motorized lens with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-412N	HYU-412N		IP dome with IR illumination of 20~30m, for outdoors 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0.01 lux. 2.8~12 mm (98°~30°) motorized lens with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67, IK10. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-494	HYU-494		IP dome with IR of 30m, for outdoors 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2.9" CMOS, 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm (97°) fixed lens. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. Intelligent functions. Facial detection. MicroSD/SDHC/SDXC. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-493	HYU-493		IP vandal dome Performance Line with IR of 30m, for outdoors 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2.9" CMOS, 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm (97°) fixed lens. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. Intelligent functions. Facial detection. MicroSD/SDHC/SDXC. IP67, IK10. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-610	HYU-610		2MP IP Alsense IP dome with IR illumination of 50m, suitable for outdoors. H.265/H.264/MJPEG. 1/2,8" CMOS, 2MP. 2MP@25 fps. ICR. 0,012 lux. 2,8 mm lens (108°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, 1 fixed ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE	Prijs op aanvraag
HYU-614	HYU-614		2MP IP Alsense dome with IR of 30m, vandal protection suitable for outdoors. H.265/H.264/MJPEG. 1/2,8" CMOS, 2MP. 2MP@25 fps. ICR. 0,009 lux. 2,8 mm lens (108°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, 1 fixed ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67, IK10. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-609	HYU-609		4MP Alsense IP dome with IR illumination of 50m, suitable for outdoors. H.265/H.264/MJPEG. 1/2,7" CMOS, 4MP. 4MP@25 fps digital resolution. ICR. 0,012 lux. 2,8 mm lens (104°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, 1 fixed ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-613	HYU-613		4MP IP Alsense dome with IR of 30m, vandal protection suitable for outdoors. H.265/H.264/MJPEG. 1/2,7" CMOS, 4MP. 4MP@25 fps. ICR. 0,012 lux. 2,8 mm lens (104°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, 1 fixed ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67, IK10. 3AXIS. 12V DC. PoE.	Prijs op aanvraag











HYU-425	HYU-425		IP dome with IR of 30m, for outdoors. H.265/H.264/MJPEG. 1/2,5" CMOS, 8MP. Triple Stream. Digital resolution of 8MP@12,5fps. ICR filter. 0,028 lux. 2,8 mm lens (102°). OSD, BLC, HLC, WDR 120dB, 3D-DNR, privacy mask, 1 ROI, image adjustment. IVS. Facial detection. MicroSD//SDHC/SDXC slot. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-677	HYU-677		IP minidome Color View series, 2MP with white illumination up to 30m, suitable for outdoors. H.265+ / H.265/ H.264+ / H.264/ MJPEG. 1/2,8" CMOS, 2MP. 1080P@25 fps. 0,0035 lux F1.0. 4 mm lens (89°). OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 fixed ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-426	HYU-426		IP dome with IR illumination of 30m, vandal protection for outdoors. H.265/H.264/MJPEG. 1/2,5" CMOS, 8MP. Triple Stream. Digital resolution of 8MP@12,5fps. ICR filter. 0,028 lux. 2,8 mm lens (102°). OSD, BLC, HLC, WDR 120dB, 3D-DNR, privacy mask, 1 ROI, image adjustment. IVS. Facial detection. MicroSD//SDHC/SDXC slot. IP67, IK10. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-620	HYU-620		IP dome, 5MP with IR of 30m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,7" CMOS, 5MP. 5MP@12,5FPS. ICR. 0,02 lux. 2,8 ~12 mm motor lens (98°~28°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection and privacy mask, 1 fixed ROI. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-619	HYU-619		IP dome, 5MP with IR of 30m, vandal protection for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,7" CMOS, 5MP. 5MP@12,5FPS. ICR filter. 0,02 lux. 2,8 ~12 mm motor lens (98°~28°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, 1 fixed ROI. Reset button. MicroSD. Onvif, ISAPI. IP67, IK10. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-394	HYU-394		WiFi vandal IP dome with IR of 10 m, for outdoors, 4MP. H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Dual Stream. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (106°). OSD, 3D-NR, BLC, real WDR 120dB, ROI. IVS. MicroSD//SDHC/SDXC. IP67, IK08. 12V DC. PoE.	Prijs op aanvraag
HYU-498	HYU-498		WiFi IP dome Performance Line with IR of 10m, for outdoors, 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,9" CMOS, 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm (80°) fixed lens. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, ROI fixed zone. Intelligent functions. Facial detection. MicroSD//SDHC/SDXC slot. IP67, IK08. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-676	HYU-676		IP minidome Color View series de 4MP with white illumination up to 20m, for outdoors. H.265+ / H.265/ H.264+ / H.264/ MJPEG. 1/1,8" CMOS, 4MP. 4MP@25 fps. 0,0014 lux F1.0. 4 mm lens (94°). OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-743	HYU-743		2MP HYUNDAI NEXTGEN IP dome with IR of 30m, vandal-proof for outdoors. H.265 + / H.265 / H.264 + / H.264 / MJPEG format. Triple stream. 1/2,8" CMOS 2MP. Digital resolution 1080P @ 25 fps. ICR filter. 0.018 lux. 2,8 ~ 12 mm motor lens with autofocus (110 ° ~ 31 °). OSD, AGC, BLC, HLC, WDR true 120dB, 3D-DNR, 1 fixed ROI zone IVS Face detection Two-way audio 1 input / 1 alarm output BNC video output Reset button MicroSD Onvif, ISAPI IP66, IK10 3AXIS 12V DC	Prijs op aanvraag
HYU-396	HYU-396		Fixed IP vandal dome, IR illumination of 30m, for outdoors, 8 MP. H.265+ /H.265 /H.264+ /H.264 /MJPEG. 1/2,5" CMOS, 8MP. Triple stream. Mechanical filter. 0,014 lux. 2,8 ~12 mm motorized lens (115°~35°). OSD, 3D-NR, BLC, real WDR 120dB, motion detection, privacy mask, 1 ROI. IVS. Audio: 1 in / 1 out. Alarm: 1 in / 1 out. MicroSD//SDHC/SDXC. IP67, IK10, Lightning-proof 2KV. 12V DC. PoE.	Prijs op aanvraag




HYU-744	HYU-744		HYUNDAI NEXTGEN IP dome of 4MP with IR of 30m, vandal-proof suitable for outdoors. H.265 + / H.265 / H.264 + / H.264 / MJPEG format. Triple stream. 1/3" CMOS of 4MP. Digital resolution of 4MP @ 25 fps. ICR filter. 0.018 lux. 2.8 ~ 12 mm motor lens with autofocus (104 ° ~ 29 °). OSD, AGC, BLC, HLC, WDR true 120dB, 3D-DNR, 1 fixed ROI zone IVS Face detection. Two-way audio. Alarm: 1 in / 1 out BNC video output Reset button MicroSD Onvif. ISAPI IP66. IK10 3AXIS 12V DC	Prijs op aanvraag
HYU-397	HYU-397		Fixed IP vandal dome with IR illumination of 30 m., for outdoor, 8 MP. H.265+ /H.265 /H.264+ /H.264 /MJPEG. 1/2,5" CMOS, 8MP. Triple stream. Mechanical filter. 0,014 lux. 2,8 ~12 mm motorized lens (115°~35°). OSD, 3D-NR, BLC, real WDR 120dB, motion detection, privacy mask, 1 ROI. IVS. Audio: 1 in / 1 out. Alarm: 1 in / 1 out. MicroSD/SDHC/SDXC. IP67, IK10, Lightning-proof 2KV. 12V DC. PoE.	Prijs op aanvraag
HYU-500	HYU-500		IP vandal dome Performance Line with IR of 30m, for outdoors, 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,9" CMOS. 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8~12 mm (88°~27°) motorized lens with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. Intelligent functions. 2 way audio. Alarm: 1 in / 1 out. MicroSD/SDHC/SDXC. IP67. IK10. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-665	HYU-665		Alsense IP dome of 2MP with IR illumination of 30 m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,8" CMOS, 2MP. 1080P@25 fps. ICR. 0,007 lux. 2,8~12 mm motor lens (113°~32°) with autofocus. OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 fixed ROI. IVS. 2 way audio. Alarm: 1 in / 1 out. Reset button. MicroSD. Onvif, ISAPI. IP67, IK10. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-406	HYU-406		IP dome Night Fighter with IR illumination of 30m, vandal protection for outdoors, 8 MP. H.265+ /H.265 /H.264+ /H.264 /MJPEG. 1/2,5" CMOS, 8MP. Triple stream. Mechanical filter. 0,01 lux. 2,8 ~12 mm (115°~35°) motor lens. OSD, 3D-NR, BLC, WDR true 120dB, motion detection, privacy mask, 1 ROI. IVS. Audio: 1 in / 1 out. Alarm: 1 in / 1 out. MicroSD/SDHC/SDXC. IP67, IK10, Lightning-proof 2KV. 12V DC. PoE.	Prijs op aanvraag
HYU-667	HYU-667		Alsense IP dome of 4MP with IR of 30m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,7" CMOS, 4MP. 4MP@25 fps. ICR. 0,01 lux. 2,8~12 mm (101°~29°) motor lens with autofocus. OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 fixed ROI . IVS. 2 way audio. Alarm: 1 in / 1 out. Reset button. MicroSD. Onvif, ISAPI. IP67, IK10. 3AXIS. 12V DC. PoE.	Prijs op aanvraag

Netwerk camera's - Bullet







Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-414	HYU-414		IP bullet camera with IR of 30m, for outdoors, 2 MP. H.265+, H.265, H.264+, H.264. 1/2,8" CMOS, 2MP. Digital resolution 1080P, 1,3MP, 720P, etc. Mechanical filter. 0,01 lux. 2,8 mm (103°) fixed lens. OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-768	HYU-768		HYUNDAI NEXT GEN IP bullet camera Performance Line with IR of 30m, 2 MP. H.265 / H.264 / MJPEG format. 1/2,8" CMOS, 2MP. Digital resolution of 1080P@25FPS. Mechanical filter. 0.028 lux. 2.8 mm lens (114.8 °). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy masks, fixed ROI zone, IP67, 3AXIS, 12V DC, PoE.	Prijs op aanvraag
HYU-408	HYU-408		IP bullet camera with IR illumination of 30m, for outdoors, 4 MP. Formato H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution: 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (100°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67. 3AXIS bracket. 12V DC. PoE.	Prijs op aanvraag

HYU-752	HYU-752		IP bullet camera with IR illumination of 30m, for outdoors, 4 MP. Formato H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution: 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (100°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67. 3AXIS bracket. 12V DC. PoE.	Prijs op aanvraag
HYU-300	HYU-300		IP fixed dome with IR illumination of 40 m, for outdoors. H.265/MJPEG. 1/2,9" Sony® CMOS 2 MP. 2MP @25/30 fps. Dual stream. 2.7 ~ 13 mm autofocus motorized lens. ICR filter. OSD, digital WDR. 2 way audio. Onvif. IP66. 12V DC. PoE. Reset button. Waterproof cable.	Prijs op aanvraag
HYU-648	HYU-648		WiFi IP bullet camera with IR of 30 m, for outdoors of 2 MP. H.265+/H.265/H.264+/H.264//MJPEG. 1/2,8" CMOS, 2MP. Dual Stream. Mechanical filter. 0,028 lux. 2,8 mm lens (114°). OSD, AGC, 3D-DNR, BLC, Digital WDR, privacy mask, ROI. Built in microphone. MicroSD/SDHC/SDXC. IP66. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-663	HYU-663		IP WiFi bullet camera with IR of 30m, for outdoors, 4 MP. H.265+/H.265/H.264+/H.264//MJPEG. 1/3" CMOS, 4MP. Dual stream. Mechanical filter. 0,028 lux. 2,8 mm lens (100°). OSD, AGC, 3D-DNR, BLC, digital WDR, privacy mask, ROI. Microphone incorporated. MicroSD/SDHC/SDXC. IP66. 3AXIS. 12V DC.	Prijs op aanvraag
HYU-771	HYU-771		HYUNDAI NEXT GEN Performance Line IP vandal bullet camera with IR of 30m, 2 MP for outdoors. H.265 / H.264 / MJPEG format. 1/2,8" CMOS, 2MP. Digital resolution 1080P @ 25FPS. Mechanical filter. 0,028 lux. 2,8 ~ 12 mm motor lens (99.6 ° ~ 35 °). OSD, AGC, BLC, WDR 120dB , 3D-DNR, motion detection, privacy masks, fixed ROI zone, intelligent analysis, IP67, 3AXIS, 12V DC, PoE.	Prijs op aanvraag
HYU-615	HYU-615		IP bullet camera, 5MP with IR illumination of 30m, suitable for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,7" CMOS, 5MP. 5MP@12,5FPS. ICR filter. 0,028 lux. 2,8 mm lens (100°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, 1 fixed ROI. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-737	HYU-737		IP HYUNDAI NEXTGEN IP bullet camera. 2MP with IR of 30m, suitable for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. Triple stream. 1/2,8" CMOS, 2MP. 1080P@25 fps. ICR filter. 0,028 lux. 2,8 mm lens (103°). OSD, AGC, BLC, HLC, WDR true 120dB, 3D-DNR, 1 fixed ROI. IVS. Face detection. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-411	HYU-411		IP bullet camera with IR illumination of 30 m, for outdoors, 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8~12 mm motor lens (98°~28°) with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. SD slot. IP67. 3AXIS bracket. Reset button. 12V DC. PoE.	Prijs op aanvraag
HYU-738	HYU-738		HYUNDAI NEXTGEN IP bullet camera of 4MP with IR of 30m, suitable for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. Triple stream. 1/3" CMOS 4MP. 4MP@25 fps. ICR filter. 0,018 lux. 2,8 mm lens (103°). OSD, AGC, BLC, HLC, WDR true 120dB, 3D-DNR, 1 fixed ROI. IVS. Facial detection. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-760	HYU-760		IP bullet camera with IR illumination of 30 m, for outdoors, 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8~12 mm motor lens (98°~28°) with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. SD slot. IP67. 3AXIS bracket. Reset button. 12V DC. PoE.	Prijs op aanvraag

HYU-492	HYU-492		IP bullet camera Performance Line with IR of 30m, for outdoors 6 MP. H.265+/H.265/H.264+/H.264+/MJPEG. 1/2,9" CMOS, 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (97°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. intelligent function. Facial detection. 2 way audio. MicroSD/SDHC/SDXC slot. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-424	HYU-424		IP bullet camera with IR of 30m, for outdoors of 8 MP. H.265+/H.265/H.264+/ H.264/MJPEG. 1/2,5" CMOS, 8MP. Triple Stream . Mechanical filter. 0,01 lux. 2,8 mm lens (102°). OSD, AGC, BLC, HLC, real WDR 120dB, motion detection and privacy mask, ROI. IVS. Facial detection. MicroSD/SDHC/SDXC. IP67. 12V DC. PoE. Reset button	Prijs op aanvraag
HYU-612	HYU-612		2 MP Aisense IP bullet camera with IR illumination 50m, suitable for outdoors. H.265/H.264/MJPEG. 1/2,8" CMOS, 2MP. 2MP@25 fps. ICR. 0,009 lux. 2,8 mm lens (104°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, 1 fixed ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE+.	Prijs op aanvraag
HYU-618	HYU-618		IP bullet camera, 5MP with IR illumination of 30m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,7" CMOS, 5MP. 5MP@12,5FPS. ICR filter. 0,02 lux. 2,8 ~12 mm motor lens (98°~28°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, 1 fixed ROI. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-679	HYU-679		IP bullet camera Color View series with 2MP with white illumination up to 30m, for outdoors. H.265+/ H.265/ H.264+/ H.264/ MJPEG. 1/2,8" CMOS, 2MP. Digital resolution of 1080P@25 fps. 0,0035 lux F1.0. 4 mm lens (89°). OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 fixed ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-203	HYU-203		IP bullet camera with IR illumination of 30 meters, for outdoors. 4MP. H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. 4MP /1080P /720P /CIF. mechanical filter. 0,014 lux. 2,8~12 mm motorized lens (112°~33,8°). OSD, 3D-NR, BLC, real WDR (120 dB), privacy mask, ROI. Intelligent functions (IVS). MicroSD//SDHC/SDXC. IP67. 12V DC. PoE.	Prijs op aanvraag
HYU-678	HYU-678		IP bullet camera Color View series of 4MP with white illumination up to 30m, for outdoors. H.265+/ H.265/ H.264+/ H.264/ MJPEG. 1/1,8" CMOS, 4MP. 4MP@25 fps. 0,0014 lux F1.0. 4 mm lens (94°). OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 fixed ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.	Prijs op aanvraag
HYU-739	HYU-739		HYUNDAI NEXTGEN IP bullet camera, 2 MP with IR of 50m, vandal protection for outdoors H.265+/ H.265/ H.264+/ H.264/MJPEG. Triple stream. 1/2,8" CMOS, 2MP. 1080P@25 fps. ICR filter. 0,018 lux. 2,8~12 mm motor lens with autofocus (110°~31°). OSD, AGC, BLC, HLC, WDR true 120dB, 3D-DNR, 1 fixed ROI. IVS. Face detection. 2 way audio. Alarm: 1 in / 1 out. BNC video output. Reset button. MicroSD. Onvif, ISAPI. IP66. IK10. 3AXIS. 12V DC. PoE+.	Prijs op aanvraag
HYU-499	HYU-499		IP vandal bullet camera Performance Line with IR illumination of 50m, for outdoors 6 MP. H.265+/H.265/H.264+/H.264+/MJPEG. 1/2,9" CMOS of 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8~12 mm (88°~27°) motorized lens with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. Intelligent functions. Facial detection. 2 way audio. Alarm: 1 in / 1 out.	Prijs op aanvraag
HYU-740	HYU-740		4MP HYUNDAI NEXTGEN IP bullet camera with 50m infrared illumination, vandal proof for outdoor use. H.265 + / H.265 / H.264 + / H.264 / MJPEG format. Triple stream. CMOS 1/3" of 4MP. Digital resolution of 4MP @ 25 fps. ICR filter. 0.018 lux. Motorized optics 2.8 ~ 12 mm with autofocus (104 ° ~ 29 °). OSD, AGC, BLC, HLC, WDR real 120dB, 3D-DNR, 1 fixed ROI zone IVS Face detection Two-way audio 1 input / 1 alarm output BNC video output Reset button MicroSD Onvif. ISAPI	Prijs op aanvraag

HYU-405	HYU-405		Night Fighter IP bullet camera with IR of 50m, for outdoors. 8 MP. H.265+ /H.265 /H.264+ /H.264 /MJPEG. 1/2,5" CMOS, 8MP. Triple stream. Mechanical filter. 0,01 lux. 2,8 ~12 mm (115°~35°) motorized lens. OSD, 3D-NR, BLC, real WDR 120dB, motion detection, privacy mask, 1 ROI zone. IVS. Audio: 1 in / 1 out. Alarm: 1 in / 1 out. MicroSD/SDHC/SDXC card slot. IP67, IK10, Lightning-proof 2KV. 12V DC. PoE+.	Prijs op aanvraag
HYU-666	HYU-666		Alsense IP bullet camera of 2MP with IR of 50m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,8" CMOS, 2MP. 1080P@25 fps. ICR filter. 0,007 lux. 2,8~12 mm (113°~32°) motor lens with autofocus. OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 fixed ROI. IVS. 2 way audio. Alarm: 1 in / 1 out. Reset button. MicroSD. Onvif, ISAPI. IP67, IK10. 3AXIS. 12V DC. PoE+.	Prijs op aanvraag
HYU-668	HYU-668		IP Alsense bullet camera of 4MP with IR 50m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,7" CMOS, 4MP. 4MP@25 fps. ICR. 0,01 lux. 2,8~12 mm motor lens (101°~29°) with autofocus. OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 fixed ROI. IVS. 2 way audio. Alarm: 1 in / 1 out. Reset button. MicroSD. Onvif, ISAPI. IP67, IK10. 3AXIS. 12V DC. PoE+.	Prijs op aanvraag

Network camera's - Speeddome

Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-625N	HYU-625N		IP StarLight motorized dome of 100°/sec. with Smart IR 20m vandal protection for outdoors. H.265+ / H.265/ H.264+ / H.264/ MJPEG. 1/3" CMOS, 2MP. Triple Stream. Digital resolution of 2MP@25FPS. ICR filter. 0,005/0,001 lux. 2,8 ~ 12 mm (109°~34°) motorized lens. 16X digital zoom. OSD, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, EIS, 2 ROI per stream, motion detection, 24 privacy mask. IVS. 2 way audio. 300 presets. MicroSD/SDHC/SDXC. Onvif. PSIA. CGI. IP66. IK10.	Prijs op aanvraag
HYU-237	HYU-237		IP motorized dome of 60°/sec with IR illumination of 20 meters, for indoors. H.264/MJPEG. 1/3" CMOS, 2MP. Dual stream. 2X optical zoom of 3.6~8.6 mm (77°~50°). 16X digital zoom. ICR. OSD, AWB, AGC, BLC, digital WDR, 3D-NR, motion detection, privacy mask, 4 ROI zones. Intelligent detection (IVS). 300 presets. Audio: 1in/1out. Alarm: 1in/ 1out. MicroSD/SDHC/SDXC. Onvif, PSIA, CG, P2P. IP54, Lightning-proof. 12V DC. PoE.	Prijs op aanvraag
HYU-626N	HYU-626N		IP motorized dome of 100°/sec. with Smart IR 15m vandal protection for outdoors. H.265+ / H.265/ H.264+ / H.264/ MJPEG. 1/3" CMOS 4MP. Triple Stream. Digital resolution 4MP@25FPS. ICR filter. 0,05/0,005 lux. 2,8 ~ 12 mm (100°~33°) motorized lens. 16X digital zoom. OSD, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, EIS, 2 ROI per stream, motion detection, 24 privacy mask. IVS. 2 way audio. 300 presets. MicroSD/SDHC/SDXC slot. Onvif. PSIA. CGI. IP66.	Prijs op aanvraag
HYU-428N	HYU-428N		IP PTZ of 80°/sec. with Smart IR of 100 m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,8" CMOS, 2 MP. Triple stream. Resolution up to 2MP. 25X optical zoom of 4,8~120 mm. 16X digital zoom. ICR. OSD, AWB, AGC, BLC, real WDR 120 dB, 3D-NR, motion detection, privacy mask, defog, 4 ROI. IVS. 300 presets. MicroSD/SDHC/SDXC. Onvif, PSIA, CGI. IP66, Lightning-proof. 12V DC. PoE+ supported. Bracket and power supply is included.	Prijs op aanvraag
HYU-688	HYU-688		IP PTZ of 80°/sec. with Smart IR of 100 m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,5" CMOS 4 MP. Triple stream. 4MP. 15X optical zoom of 5~75 mm. 16X digital zoom. ICR filter. OSD, AWB, AGC, BLC, WDR true 120 dB, 3D-NR, motion detection, privacy mask, defog. IVS. 300 presets. MicroSD/SDHC/SDXC. Onvif, ISAPI, SDK. IP66, Lightning-proof. 12V DC. PoE+ supported. Bracket and power supply included.	Prijs op aanvraag
HYU-688N	HYU-688N		80° / sec IP motorized dome. with Smart IR of 100 m, for outdoors. H.265 + / H.265 / H.264 + / H.264 / MJPEG format. 1 / 2,8 "4 megapixel CMOS. Triple stream. Resolution up to 4MP @ 25IPS. 15X optical zoom 5 ~ 75mm. 16X digital zoom. ICR filter. OSD, AWB, AGC, BLC, 120 dB real WDR, 3D-NR, video sensor, privacy masks, defog. Intelligent detection (IVS). 300 presets. MicroSD / SDHC / SDXC slot. Onvif, ISAPI, SDK. IP66. Lightning-proof. 12V DC. Supports PoE+. Includes	Prijs op aanvraag




NEW

HYU-386	HYU-386		IP motorized dome Starlight of 120°/sec. with Smart IR of 150 m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,8" CMOS, 2 MP. Triple Stream. 2MP resolution. 25X optical zoom of 4,8-120 mm (57,6°-2,5°). 16X digital zoom. ICR filter. OSD, AWB, ATW, AGC, BLC, HLC, real WDR 120 dB, 3D-DNR, EIS, motion detection, privacy mask, defog, 4 ROI per stream. IVS. 300 presets. MicroSD/SDHC/SDXC slot. Onvif, PSIA, CGI, IP66, Lightning-proof, 24V AC, Hi-PoE supported.	Prijs op aanvraag
HYU-690	HYU-690		IP PTZ of 160°/sec. with Smart IR of 150 m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,8" CMOS, 2 MP. Triple Stream. 1080P. 32X optical zoom 4,8-153 mm. 16X digital zoom. ICR filter. OSD, AWB, AGC, BLC, WDR true 120 dB, 3D-NR, motion detection, privacy mask, defog. IVS. 300 presets. MicroSD/SDHC/SDXC. Onvif, ISAPI, CGI. IP66, Lightning-proof. 24V AC. Hi-PoE supported. Bracket and power supply is not included.	Prijs op aanvraag
HYU-691	HYU-691		IP PTZ of 160°/sec. with Smart IR of 150 m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/1,9" CMOS, 4 MP. Triple Stream. 4MP. 30X optical zoom 5,9-177 mm. 16X digital zoom. ICR. OSD, AWB, AGC, BLC, digital WDR, 3D-NR, motion detection, privacy mask, defog. IVS. 300 presets. MicroSD/SDHC/SDXC. Onvif, ISAPI, CGI. IP66, Lightning-proof. 24V AC. Hi-PoE supported. Bracket and power supply is not included.	Prijs op aanvraag

Network camera's - Fisheye & Panoramische camera's



Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-484	HYU-484		Indoor IP PTZ (30°/sec.) with 3 fixed cameras and 1 motorized. IR of Ø20 m. H.265/H.264/MJPEG. 1/2,8" CMOS, 2 MP. 2MP. 3x 2 mm fixed cameras(128,5°) + 1 motorized camera with optical zoom 4X de 2,8-12 mm (120°-56,6°). Filtro ICR. 0,05/0,01 lux. OSD, AWB, AGC, BLC, HLC, digital WDR, 3D-DNR, 8 ROI, motion detection, privacy mask, defog. 300 presets. MicroSD/SDHC/SDXC. Onvif, ISAPI, CGI. Lightning-proof 2KV, 12V DC, PoE+ supported. Power supply and stand	Prijs op aanvraag
HYU-544	HYU-544		IP fisheye vandal dome with IR of 15m, for outdoors. H.264/MJPEG. Digital resolution: 12MP (4000x3072), etc. 1,98 mm fisheye lens, 360°. OSD, AGC, BLC, digital WDR, 3D-DNR, 4 ROI. IVS. MicroSD/SDHC/SDXC. IP66, IK10. 12V DC. PoE.	Prijs op aanvraag

Network camera's - Verborgen & mini camera's


Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-432N	HYU-432N		WiFi compact IP camera with IR illumination of 5 m for indoors. H.264. 1/2,8" CMOS, 2MP. Dual stream. Mechanical filter. 0,01 lux. 2,8 mm fixed lens. OSD, AGC, 3D-NR, digital WDR. Built in microphone and speaker. MicroSD/SDHC/SDXC. 5V DC.	Prijs op aanvraag
HYU-605N	HYU-605N		WiFi compact IP camera with PAN/TILT (low speed) IR illumination of 5 m for indoor. H.264. 1/2,8" CMOS, 2MP. Dual Stream. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (105,8°). OSD, AGC, 3D-NR, BLC, digital WDR. Built in microphone and speaker. MicroSD/SDHC/SDXC. 5V DC.	Prijs op aanvraag
HYU-630	HYU-630		WiFi compact IP camera with PIR of 10 m (90°) and IR illumination of 10 m for indoors. H.265+/ H.265/ H.264+/ H.264/ MJPEG. 1/2,8" CMOS, 2MP. Dual Stream. Mechanical filter. 0,028 lux. 2,8 mm lens (115,6°). OSD, 3D-DNR, BLC, HLC, WDR true 120 dB, ROI. IVS. Facial detection. Microphone and speaker incorporated. MicroSD//SDHC/SDXC. 12V DC. PoE.	Prijs op aanvraag
HYU-401	HYU-401		Day/night IP camera. H.264/MJPEG. 1/4" CMOS, 1MP. 720P @30 fps. 2,8 mm fixed lens. Electronic filter. 0,028 lux. OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection and privacy mask. IVS. Onvif. 12V DC.	Prijs op aanvraag

HYU-496	HYU-496		WiFi IP compact camera with IR of 10m, for indoors, 4 MP. H.265+ /H.265 /H.264 /H.264+ /MJPEG. 1/3" CMOS, 4MP. 4MP, 3MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm (98°) fixed lens. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, ROI zones. Intelligent functions. Facial detection. 2 way audio. MicroSD/SDHC/SDXC. 12V DC. PoE.	Prijs op aanvraag
HYU-404	HYU-404		Day/night IP camera. H.265/H.264/MJPEG. 1/2,7" CMOS. 2MP. 1080P @30 fps. 3,7 mm lens (78°). Electronic filter. 0,025/0,005 lux. OSD, AGC, real WDR 120dB, 3D-DNR, 1 ROI. IVS, facial detection. 1 audio in. Onvif. 12V DC. Reset button.	Prijs op aanvraag
HYU-495	HYU-495		WiFi IP compact camera Performance Line with IR illumination of 10m, for indoors, 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,8" CMOS, 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm (80°) fixed lens. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. Intelligent functions. Facial detection. 2 way audio. MicroSD/SDHC/SDXC. 12V DC. PoE.	Prijs op aanvraag

Network camera's - Kentekenherkenning

Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-444	HYU-444		IP bullet camera Night Fighter series with Smart IR of 50m, for outdoors, 2 MP. Triple stream. H.264/H.264+/MPEG4/MJPEG. 1/1,8" CMOS, 2MP. Digital resolution 1080P, 1,3MP, 720P. Mechanical filter. 0,0027 lux. 2,8~12 mm (92°~32°) motorized lens with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, ROI, motion detection, ROI, defog. OCR function, Integrated LPR. IVS. Facial detection. 2 way audio. Alarm: 1 in / 1 out. MicroSD slot. IP67. 3AXIS bracket. Reset button. 12V DC. PoE.	Prijs op aanvraag
HYU-652	HYU-652		IP bullet camera Night Fighter with Smart IR 50m, for outdoors 2 MP. Triple Stream. H.264/MPEG4/MJPEG. 1/1,8" CMOS, 2MP. Digital resolution 1080P, 1,3MP, 720P. Mechanical filter. 0,0027 lux. 8~32 mm motor lens with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, ROI, motion detection, ROI, defog. LPR function, integrated LPR. IVS. Facial detection. 2 way audio. Alarm: 1 in / 1 out. MicroSD slot. IP67. 3AXIS bracket. Reset button. 12V DC. PoE. Bracket and tube base	Prijs op aanvraag


Network camera's - Mensen tellen











Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-519	HYU-519		IP smart camera for people counting. H.264. Dual stream. 1/3" CMOS. 640x960 resolution. 2 mm lens (100°) and 2,8 mm lens (82°). 3D-DNR, 1 ROI per stream, Brightness adjustments. Alarm: 1 in / 1 out. 12V DC. PoE.	Prijs op aanvraag

Thermische camera's

[BULLET CAMERA](#)
[DOMES](#)


Thermische camera's - Bullet camera

Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-660	HYU-660		Thermal bullet camera Thermal-Line for outdoors. Thermal camera with 160 x 120 resolution, 3,1 mm thermal lens. People detection up to 53 meters and vehicles up to 162 meters. VCA. Video output IP/ANALOG. Audio: 1 in / 1 out. Alarm: 2 in / 2 out. MicroSD card. Lightning-proof 6KV. IP66. 12V DC. PoE.	Prijs op aanvraag

HYU-661	HYU-661		Thermal bullet camera Thermal-Line for outdoors. Thermal camera with 160 x 120 resolution, 6,2 mm thermal lens. People detection up to 182 meters and vehicles up to 559 meters. VCA. IP/ANALOG video output. Audio: 1 in / 1 out. Alarm: 2 in / 2 out. MicroSD slot. Lightning-proof 6KV. IP66. 12V DC. PoE.	Prijs op aanvraag
HYU-745	HYU-745		HYUNDAI NEXTGEN Thermal bullet + visible camera Thermal-Line series with IR illumination of 40 m, for outdoor. Visible camera with 1/2.8" CMOS of 2 megapixels. 4mm visible optic. Thermal camera with resolution 160 x 120, thermal lens of 3.1 mm. Detection of people up to 91 meters and vehicles up to 280 meters. Digital WDR, 3D-DNR. Intelligent detection (VCA). IP / ANALOG video output. Audio: 1 input / 1 output. Alarm: 2 inputs / 2 outputs. RS485 port MicroSD slot Onvif. API. ISAPI.	Prijs op aanvraag
HYU-746	HYU-746		HYUNDAI NEXTGEN Thermal bullet + visible camera Thermal-Line series with IR illumination of 40 m, for outdoor. Visible camera with 1/2.8" CMOS of 2 MP. 6 mm visible lens. Thermal camera with 160 x 120 resolution, 6,2 mm thermal lens. Detection of people up to 182 meters and vehicles up to 559 meters. Digital WDR, 3D-DNR. Intelligent detection (VCA). IP / ANALOG video output. Audio: 1 input / 1 output. Alarm: 2 inputs / 2 outputs. RS485 port MicroSD slot Onvif. API. ISAPI.	Prijs op aanvraag
HYU-555	HYU-555		Thermal + visible bullet camera Thermal-Line with IR of 30 m, for outdoors. Visible camera with 1/2,8 CMOS, 2 MP. 6 mm visible lens. Thermal camera with 160 x 120 resolution, 7 mm thermal lens. People detection up to 140 meters and vehicles up to 429 meters. Digital WDR, 3D-DNR. VCA. IP/ANALOG video output. Audio: 1 in / 1 out. Alarm: 2 in / 2 out. MicroSD. Onvif, PSIA, CGI. Lightning-proof 6KV. IP67. 24V AC, 12V DC. PoE+.	Prijs op aanvraag
HYU-556	HYU-556		Thermal+visible bullet camera Thermal-Line with IR of 30 m, for outdoors. Visible camera with 1/2,8 CMOS, 2 MP. 8 mm visible lens. 160 x 120 thermal camera resolution, 10 mm thermal lens. People detection up to 200 m and vehicles up to 613 m. WDR digital, 3D-DNR. VCA. IP/ANALOG video output. Audio: 1 in / 1 out. Alarm: 2 in / 2 out. MicroSD slot. Onvif, PSIA, CGI. Lightning-proof 6KV. IP67. 24V AC, 12V DC. PoE+.	Prijs op aanvraag
HYU-439	HYU-439		IP thermal camera, Thermal Line with integrated GPU. 384 x 288 resolution. 7 mm lens. People detection up to 206 meters and vehicles up to 631 meters. Temperature measurement up to 164m. Fire detection up to 412m. BNC video output. AGC, 3D-DNR. Audio: 1 in / 1 out. Alarm: 2 in / 2 out. Ranura MicroSD. IP66. Heater. 24V AC, 12V DC. PoE+. Bracket included and tube base.	Prijs op aanvraag
HYU-440	HYU-440		IP thermal camera, Thermal Line with integrated GPU. 384 x 288 resolution. 10 mm lens. People detection up to 294 meters and vehicles up to 902 meters. Temperature measurement up to 234m. Fire detection up to 588m. BNC video output. AGC, 3D-DNR. Audio: 1 in / 1 out. Alarm: 2 in / 2 out. Ranura MicroSD. IP66. Heater. 24V AC, 12V DC. PoE+. Bracket included and tube base.	Prijs op aanvraag
HYU-441	HYU-441		IP thermal camera, Thermal Line with integrated GPU. 384 x 288 resolution. 15 mm lens. People detection up to 441 meters and vehicles up to 1353 meters. Temperature measurement up to 351m. Fire detection up to 882m. BNC video output. AGC, 3D-DNR. Audio: 1 in / 1 out. Alarm: 2 in / 2 out. Ranura MicroSD. IP66. Heater. 24V AC, 12V DC. PoE+. Bracket included and tube base.	Prijs op aanvraag
HYU-442	HYU-442		IP thermal camera, Thermal Line with integrated GPU. 384 x 288 resolution. 25 mm lens. People detection up to 735 meters and vehicles up to 2255 meters. Temperature measurement up to 585 m. Fire detection up to 1470 m. BNC video output. AGC, 3D-DNR. Audio: 1 in / 1 out. Alarm: 2 in / 2 out. Ranura MicroSD. IP66. Heater. 24V AC, 12V DC. PoE+. Bracket included and tube base.	Prijs op aanvraag
HYU-443	HYU-443		IP thermal camera, Thermal Line with integrated GPU. 384 x 288 resolution. 35 mm lens. People detection up to 1029 meters and vehicles up to 3157 meters. Temperature measurement up to 829m. Fire detection up to 2058m. BNC video output. AGC, 3D-DNR. Audio: 1 in / 1 out. Alarm: 2 in / 2 out. Ranura MicroSD. IP66. Heater. 24V AC, 12V DC. PoE+. Bracket included and tube base.	Prijs op aanvraag

HYU-747	HYU-747		HYUNDAI NEXTGEN thermal bullet + visible camera Thermal-Line series with IR of 40 m, for outdoors. Visible camera with 1/2.8" CMOS of 2 MP. 8 mm visible lens. Thermal camera with resolution 384 x 288, 15 mm thermal lens. Detection of people up to 441 meters and vehicles up to 1353 meters. Digital WDR, 3D-DNR. Intelligent detection (VCA). IP / ANALOG video output. Audio: 1 input / 1 output. Alarm: 2 inputs / 2 outputs. MicroSD slot Onvif, API, ISAPI, Lightning-proof 6KV.	Prijs op aanvraag
-------------------------	---------	---	--	-------------------




Thermische camera's - Domes











Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-659	HYU-659		Thermal+visible dome Thermal-Line with IR of 15 m, for outdoors. Visible camera for 1/2,7 CMOS, 2 MP. Visible lens of 2,1 mm. Thermal camera with 160 x 120, thermal lens of 1,8 mm. People detection up to 53 meters and vehicles up to 162 meters. WDR 120dB, 3D-DNR. VCA. IP/ANALOG video output. Audio: 1 in / 1 out. Alarm: 1 in / 1out . MicroSD slot. Lightning-proof 6KV. IP67. 12V DC. PoE.	Prijs op aanvraag







Network recorders

[NETWORK RECORDERS](#)
[WIFI NETWORK RECORDERS](#)



Network recorders - Network recorders

Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-525	NVR3104P		4 channels IP NVR. H.265+/H.265/H.264+/H.264. 1 channel 4MP or 2 channel 1080P. Display up to 4MP. Recording: 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. 40 Mbps. VGA and HDMI output at 1080P. 1 HDD SATA. 2 USB. Compatible with Onvif, P2P, DDNS. 12V DC. Desktop.	Prijs op aanvraag
HYU-526	NVR3108P		8 CH IP NVR. H.265+/H.265/H.264+/H.264. 1 CH @ 4MP or 2 CH @ 1080P. Display up to 4MP. Recording: 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. 60 Mbps. VGA and HDMI output @ 1080P. 1 HDD SATA supported. 2x USB. Compatible with Onvif, P2P, DDNS. 12V DC. Desktop.	Prijs op aanvraag
HYU-755	NVR3104M-4P-4K		4CH HYUNDAI NEXTGEN IP NVR. H.265/H.265+/H.264/H.264+/MPEG4. 4-ch synchronous playback. Display up to 8MP. Recording 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. Up to 40 Mbps recording. HDMI 4K and VGA 1080P output. 2 way audio. Supports 1 SATA HDD. RJ45 Gigabit Compatible Onvif, P2P, DDNS. 12V DC 4 PoE +.	Prijs op aanvraag
HYU-523	NVR3104P-4P		4 channel IP NVR. H.265+/H.265/H.264+/H.264. 1 ch 4MP or 2 ch 1080P. 4MP display. Recording: 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. 40 Mbps. VGA and HDMI at 1080P. 1 HDD SATA. 2 USB. Compatible Onvif, P2P, DDNS. 48V DC. Desktop. 4x PoE+.	Prijs op aanvraag
HYU-445	NVR3104M-4P-4KLITE		4 channel IP NVR. H.265/H.265+/H.264/H.264+/MPEG4. 4 channel 1080P or 1 channel 8MP. Display up to 8MP. Recording: 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, 4CIF, etc. Recording up to 40 Mbps. VGA @ 1080P and HDMI @ 4K output. Two way audio. 1 HDD SATA supported. Onvif, P2P, DDNS. 12V DC. Desktop	Prijs op aanvraag
HYU-524	NVR3108P-8P		8 channel IP NVR. H.265+/H.265/H.264+/H.264. 1 ch 4MP or 2 ch 1080P. 4MP display. Recording: 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. 60 Mbps. VGA and HDMI at 1080P. 1 HDD SATA. 2 USB. Compatible Onvif, P2P, DDNS. 12V DC. Desktop. 8x PoE+.	Prijs op aanvraag

HYU-735	NVR4208M		8-channel HYUNDAI NEXTGEN IP NVR. H.265 / H.265 + / H.264 / H.264 + / MPEG4. 8-channel synchronous playback Display up to 8MP. Recording 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. Recording up to 80 Mbps. HDMI 4K and VGA 1080P output. Bidirectional audio. 4 inputs / 1 alarm output. Supports 2 SATA HDD. RJ45 Gigabit Compatible Onvif, P2P, DDNS. 12V DC	Prijs op aanvraag
HYU-756	NVR3108M-8P-4K		8 CH HYUNDAI NEXTGEN IP NVR. H.265/H.265+/H.264/H.264+/MPEG4. 8 CH synchronous playback Display up to 8MP. Recording 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. Recording up to 80 Mbps. HDMI 4K and VGA 1080P output. 2 way audio. Supports 1 SATA HDD. RJ45 Gigabit Compatible Onvif, P2P, DDNS. 12V DC 8 PoE +.	Prijs op aanvraag
HYU-734	NVR4216M		16 CH HYUNDAI NEXTGEN IP NVR. H.265 / H.265 + / H.264 / H.264 + / MPEG4. Synchronous playback of 16 channels. Display up to 8MP. Recording 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. Recording up to 160 Mbps. HDMI 4K and VGA 1080P output. Bidirectional audio. Alarm: 4 in / 1 output. Supports 2 SATA HDD. RJ45 Gigabit Compatible Onvif, P2P, DDNS. 12V DC	Prijs op aanvraag
HYU-280N	NVR4104M-4P-4K		4 channel IP NVR. H.265/H.264/MPEG4. Up to 4 channel 1080P. 8MP display. 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, 4CIF, etc. Recording up to 40 Mbps. VGA at 1080P and HDMI at 4K output. 2 way audio. 1 HDD SATA supported. Onvif, P2P, DDNS. 48V CC. Desktop. 4 PoE+ ports.	Prijs op aanvraag
HYU-733	NVR4232M-4K		32 ch NYUNDAI NEXTGEN IP NVR. H.264 +. Synchronous playback of up to 16 channels. Display up to 6MP. Recording 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. Recording of up to 160 Mbps. HDMI and VGA outputs at 1080P. Bidirectional audio. 4 inputs / 1 alarm output. Supports 2 SATA HDD. RJ45 Gigabit VCA Compatible Onvif, P2P, DDNS. 12V DC	Prijs op aanvraag
HYU-754	NVR3116M-16P-4K		16 ch HYUNDAI NEXTGEN IP NVR. H.265/H.265+/H.264/H.264+/MPEG4. Synchronous playback of 16 channels. Display up to 8MP. Recording 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. Recording up to 160 Mbps. HDMI 4K and VGA 1080P output. 2 way audio. Supports 2 SATA HDD. RJ45 Gigabit Compatible Onvif, P2P, DDNS. 12V DC 16 PoE +.	Prijs op aanvraag
HYU-281	NVR4208M-8P-4K		8 channel IP NVR. H.265/H.264+/H.264/MPEG4. 8 channel 1080P playback. 8MP display. Resolution 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, 4CIF, etc. 80 Mbps recording. VGA at 1080P and HDMI at 4K output. 2 way audio. Alarm: 4 in / 1 out. 2 HDD SATA supported. RJ45 Gigabit. Compatible with Onvif, P2P, DDNS. 220V AC. 8 PoE+ ports.	Prijs op aanvraag
HYU-473	NVR5208-8P-4K/POS		8 channel IP NVR with POS function. H.265/H.264+/H.264/MPEG4. 8 channel playback @ 1080P. Display up to 8MP. Recording 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, 4CIF, etc. Recording up to 80 Mbps. VGA @ 1080P and HDMI @ 4K output. 2 way audio. Alarm: 4 in / 1 out. 2 HDD SATA supported. RJ45 Gigabit. Up to 4 POS . 1 LPR channel supported. Compatible with Onvif, P2P, DDNS. 220V AC. 8 PoE+ ports.	Prijs op aanvraag
HYU-282	NVR4216M-16P-4K		16 channel IP NVR. H.265/H.264/H.264+/MPEG4. 16 channel 1080P playback. 8MP display. Recording 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, 4CIF, etc. Recording up to 160 Mbps. VGA 1080P and HDMI 4K output. 2 way audio. Alarm: 4 in / 1 out. 2 HDD SATA supported. RJ45 Gigabit. Compatible with Onvif, P2P, DDNS. 220V AC. 16 PoE+ ports.	Prijs op aanvraag
HYU-520	NVR5216-16P-4K/POS		16 CH IP NVR IP. H.265/H.264/MPEG4. 16 CH @ 1080P. Display up to 12MP. Recording: 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. Recording 160 Mbps. VGA @ 1080P and HDMI @ 4K. 2 way audio. Alarm: 4 in / 1 out. 2 HDD SATA. RJ45 Gigabit. POS function up to 4 POS. 1 LPR channel supported. Compatible with Onvif, P2P, DDNS. 220V AC. 16 PoE+ ports.	Prijs op aanvraag

HYU-634	NVR7208-8P-AI		8 channel Aisense IP NVR. H.265/H.265+/H.264/H.264+/MPEG4. playback up to 8 ch at 1080p. 8MP display. Recording: 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. Recording up to 80 Mbps. VGA at 1080P and HDMI at 4K. BNC video output. 2 way audio. Alarm: 4 in / 1 out. 2 HDD SATA supported. RJ45 Gigabit. POS function. IVS: 4 ch of false alarm filters. Compatible with Onvif, P2P, DDNS, 220V AC, 8 PoE+ ports.	Prijs op aanvraag
HYU-634N	HYU-634N			Prijs op aanvraag
HYU-654	NVR7216-16P-AI		16 channel Aisense IP NVR. H.265/H.265+/H.264/H.264+/MPEG4. playback up to 12 ch at 1080p. 8MP display. Recording: 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. Recording up to 160 Mbps. VGA at 1080P and HDMI at 4K. BNC video output. 2 way audio. Alarm: 4 in / 1 out. 2 HDD SATA supported. RJ45 Gigabit. POS function. IVS: 4 ch of false alarm filters. Compatible with Onvif, P2P, DDNS, 220V AC, 16 PoE+ ports.	Prijs op aanvraag
HYU-654N	HYU-654N			Prijs op aanvraag
HYU-382	NVR5432-16P-4K/IVS		32 ch IP NVR. H.265+/H.265/H.264+/H.264/MPEG4. Playback up to 16 channels. Display up to 8MP. Recording 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1/4CIF, etc. 256/160 Mbps. VGA output at 1080P and HDMI at 4K. 2 way audio. Alarm: 16 in / 4 out. 4 HDD SATA supported. Compatible with Onvif, P2P, DDNS and IP cameras, intelligent VCA. 220V AC. 1,5U. 16x PoE+.	Prijs op aanvraag
HYU-736	NVR7864-4K		64 channel IP NVR. H.265+ / H.265 / H.264+ / H.264 / MPEG4. Play up to 16 channels. Display up to 8MP. Recording 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1 / 4CIF, etc. 320/256 Mbps. 2 VGA outputs and 2 HDMI outputs. Bidirectional audio. 16 inputs / 4 alarm output. Supports 8 SATA HDD. Compatible Onvif, P2P, DDNS and VCA smart IP cameras. 220V AC 2U.	Prijs op aanvraag

Netwerk recorders - Wifi netwerk recorders




Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-707	NVR3104-WIFI		4-channel WiFi IP NVR. H.265 + / H.265 / H.264 + / H.264. Display up to 4MP. 4MP, 3MP, 1080P, 1.3MP, 720P recording. Recording of up to 50 Mbps. VGA outputs at 1080P and HDMI at 1080P. Supports 1 SATA HDD. WiFi antenna 2x2 MIMO. RJ45 Fast Ethernet. 12V DC	Prijs op aanvraag
HYU-708	NVR3108-WIFI		8-channel WiFi IP NVR. H.265 + / H.265 / H.264 + / H.264. Display up to 4MP. 4MP, 3MP, 1080P, 1.3MP, 720P recording. Recording of up to 50 Mbps. VGA outputs at 1080P and HDMI at 1080P. Supports 1 SATA HDD. WiFi antenna 2x2 MIMO. RJ45 Fast Ethernet. 12V DC	Prijs op aanvraag

Control Center & Keyboards

[KEYBOARD & JOYSTICK](#)

Control Center & Keyboards - Keyboard & Joystick

Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
------------	---------	------------	--------------	-----------

HYU-195N	HYU-195N		4AXIS keyboard for control of DVR/DVS, matrix, cameras and domes, etc. Can supply up to 1000 devices. 128x64 LCD display. 12V DC.	Prijs op aanvraag
HYU-354	HYU-354		4AXIS IP keyboard for DVR/DVS, NVR, matrix, cameras and IP dome, etc. Up to 1000 devices. 128x64 LCD screen. 12V DC.	Prijs op aanvraag
HYU-579	HYU-579		IP WiFi 4AXIS keyboard for control of DVR/DVS, NVR, matrix, IP domes and cameras, etc. DVI/HDMI output. Display up to 16 channels. Up to 200 device management. LCD screen 1024x600. 12V DC.	Prijs op aanvraag

Monitoren

[DESKTOP MONITOREN](#)




[PROFFESIONELE MONITOREN](#)











[VIDEOWALL](#)

Monitoren - Desktop monitoren

Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-810	HYU-810		19.5 "LED monitor. 16: 9. 1600 x 900 native resolution. 1 HDMI, 1 VGA.	Prijs op aanvraag
HYU-824	HYU-824		28 "4K LED Monitor. 16: 9. 3840 x 2160 Native Resolution. 1 Display Port, 1 HDMI. Slim Bezel. 300nits 4K Panel. Supports Image Rotation. VESA or Desktop Mount. 220V AC	Prijs op aanvraag

Monitoren - Professionele monitoren

Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-457	HYU-457		15" LED Monitor. 4:3. 1024 x 768 resolution. 1 HDMI, 2 BNC, 1 VGA. 1 BNC output. Include 2x3W speakers. Operation 24x7. MTBF 50.000 hours.	Prijs op aanvraag
HYU-685N	HYU-685N		21.5 "HYUNDAI LED monitor. 16: 9. 1080P native resolution of 1920 x 1080. 1 HDMI, 1 VGA, 1 audio output. VESA 75x75.	Prijs op aanvraag
HYU-686N	HYU-686N		23.8 "LED monitor. 16: 9. 1080P 1920 x 1080 native resolution. 1 HDMI, 1 VGA, 1 audio input. VESA 75x75.	Prijs op aanvraag

HYU-273	HYU-273		10,5" LED monitor. 1280 x 800 native resolution. 1 HDMI, 1 BNC, 1 VGA, 1 audio input, USB. 1 BNC output. Stand, current adapter, audio and VGA cable included	Prijs op aanvraag
HYU-537	HYU-537		10,4" LED monitor. 4:3. 800 x 600 native resolution. 1 HDMI, 2 BNC, 1 VGA. 1 BNC. 2x3W built in speakers. 24x7.	Prijs op aanvraag
HYU-533	HYU-533		22" LED monitor. 16:9. 1920 x 1080 native resolution. 1 HDMI, 2 BNC, 1 VGA. 1 BNC output. 2x3W built in speakers. 24x7. MTBF 50.000 hours.	Prijs op aanvraag
HYU-459	HYU-459		22" LED monitor. 16:9. Native resolution 1920 x 1080. 1 HDMI, 1 BNC, 1 VGA. 1x BNC output. Allows direct connection supported of CVI/TVI/AHD cameras in the HD BNC input till 5.0MP. Operation 24x7. MTBF 50.000 hours	Prijs op aanvraag
HYU-919	HYU-919		28 "HYUNDAI 4K LED monitor. 16: 9 aspect ratio. 3840 x 2160 native resolution. 2 Display Port, 2 HDMI. 4K panel. VESA 100 or desktop mount. 12V DC	Prijs op aanvraag
HYU-621	HYU-621		23,6" LED monitor. Native resolution of 1920 x 1080. 1 HDMI, 1 BNC input, 1 BNC output, 1 VGA, audio. 2x2W speakers. 24x7. Power supply cable, VGA cable and stand included	Prijs op aanvraag
HYU-684	HYU-684		28" LED monitor. 16:9. 4K of 3840 x 2160. 1 CVBS inputs, 1 Display Port, 1 HDMI, 1 DVI, 1 VGA. VESA 100x100. 24x7 working.	Prijs op aanvraag
HYU-534N	HYU-534N		32" LED monitor. 16:9. Native resolution 1920 x 1080. 3 BNC input, 1 video input components, 1 HDMI, 1 VGA, 1 DVI, 2 BNC output. 24x7.	Prijs op aanvraag
HYU-536N	HYU-536N		43" LED monitor. 16:9. 1920 x 1080. 5 BNC input, 1 video input, 1 HDMI, 1 VGA, 1 DVI, 1 BNC output. 24x7.	Prijs op aanvraag
HYU-535	HYU-535		43" 4K LED monitor. 16:9. 3840 x 2160 native resolution. 1 HDMI, 1 DP (Display Port), 1 DVI, 1 VGA. 2x3W built in speaker. 24x7. MTBF of 50.000 hours.	Prijs op aanvraag

HYU-538	HYU-538		55" 4K LED monitor. 16:9. 3840 x 2160 native resolution. 1 HDMI, 1 DP (Display Port), 1 DVI, 1 VGA. 2x3W built in speakers. 24x7. MTBF of 50.000 hours.	Prijs op aanvraag
-------------------------	---------	---	---	-------------------

Monitoren - Videowall










Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-539	HYU-539		46" LED unit for videowall. 16:9. Panel D-LED DID. 3,5 mm internal besel. 1920 x 1080 native resolution. 1 HDMI, 1 DP (Display Port), 1 BNC, 1 VGA. 1 BNC output. 1 in / 2 out RJ45. USB port. 24x7. MTBF of 60.000 hours.	Prijs op aanvraag
HYU-540	HYU-540		55" LED unit for videowall. 16:9. Panel D-LED DID. Internal besel of 3,5 mm. 1920 x 1080 native resolution. 1 HDMI, 1 DP (Display Port), 1 BNC, 1 VGA. 1 BNC output. 1 in / 2 out RJ45. USB port. 24x7. MTBF of 60.000 hours	Prijs op aanvraag











Accessoires











BEHUIZINGEN & CAMERASTEUNEN











Accessoires - Behuizingen & camerasteunen










Referentie	Artikel	Afbeelding	Omschrijving	Prijs (€)
HYU-574	DS-2102ZJ		Wall mount for counting people camera HYU-519	Prijs op aanvraag
HYU-693	DS-2102ZJ-WHITE		Wall mount for people counting camera HYU-519	Prijs op aanvraag
HYU-172	HYU-172		Deep base for HYU-22N, HYU-42N, HYU-43N, HYU-55, HYU-55N, HYU-58, HYU-182, HYU-171	Prijs op aanvraag
HYU-472	HYU-472		Junction box for HYU-186	Prijs op aanvraag
HYU-200N	DS-1260ZJ		Junction box for HYUNDAI and HiWatch™ HIKVISION® bullet cameras.	Prijs op aanvraag

<u>HYU-152</u>	HYU-152		Deep base for HYU-83, HYU-180, HYU-185, HYU-190	Prijs op aanvraag
<u>HYU-153</u>	HYU-153		Deep base for HYU-98, HYU-102, HYU-103, HYU-178, HYU-188	Prijs op aanvraag
<u>HYU-27</u>	HYU-27		TUBE BASE FOR DOME HYU-14N, HYU-15N, HYU-96, HYU-97, HYU-101, HYU-177, HYU-187	Prijs op aanvraag
<u>HYU-197N</u>	DS-1280ZJ-DM18		Junction box for HYUNDAI cameras	Prijs op aanvraag
<u>HYU-543</u>	HYU-543		Junction box for HYU-453 and HYU-454 cameras.	Prijs op aanvraag
<u>HYU-884</u>	HYU-884		HYUNDAI CONNECTION BASE FOR HYU-454N	Prijs op aanvraag
<u>HYU-24</u>	HYU-24		Base for HYU-11N, HYU-19N, HYU-20N, HYU-37, HYU-179, HYU-184, HYU-189	Prijs op aanvraag
<u>HYU-253</u>	HYU-253		Wall mount for HYU-247, HYU-257	Prijs op aanvraag
<u>HYU-774</u>	HYU-774		Adapter plate for HYU-202.	Prijs op aanvraag
<u>HYU-835</u>	HYU-835		Support for HYUNDAI and AirSPACE Minidomes	Prijs op aanvraag
<u>HYU-215N</u>	DS-1602		Wall bracket for HYUNDAI and HiWatch™ HIKVISION® domes. Aluminum. Indoor / outdoor	Prijs op aanvraag

<u>HYU-332</u>	HYU-332		Connection base for HYU-55N, HYU-100N, HYU-100, HYU-171, HYU-181, HYU-182, HYU-183, HYU-330, HYU-331	Prijs op aanvraag
<u>HYU-355</u>	HYU-355		Junction box base for HYU-333, HYU-336, HYU-337	Prijs op aanvraag
<u>HYU-839N</u>	DS-1280ZJ-XS-BLACK		Base for HYUNDAI domes. Aluminum alloy material with surface spray treatment. Wiring hole in bracket. 4.5 kg capacity.	Prijs op aanvraag
<u>HYU-218N</u>	DS-1661ZJ		Ceiling bracket for HYUNDAI and HiWatch™ HIKVISION® dome. Aluminum. Indoor/outdoor	Prijs op aanvraag
<u>HYU-25</u>	HYU-25		- Wall support for domes HYU-12, HYU-23, HYU-44, HYU-45	Prijs op aanvraag
<u>HYU-248N</u>	DS-1280ZJ-XS		Junction box for HYUNDAI and HiWatch™ HIKVISION® cameras.	Prijs op aanvraag
<u>HYU-30</u>	HYU-30		- Wall mount for HYU-11N, HYU-19N, HYU-20N, HYU-37, HYU-83, HYU-179, HYU-180, HYU-184, HYU-185, HYU-189, HYU-190	Prijs op aanvraag
<u>HYU-840</u>	DS-1281ZJ-DM23-BLACK		Inclined base for HYUNDAI domes. Aluminium alloy. Cable entry. Capacity of 4.5 kg. Suitable interior and exterior.	Prijs op aanvraag
<u>HYU-844</u>	HYU-844		Aluminum connection base with tube inlet for AirSpace and HYUNDAI bullet cameras. White color	Prijs op aanvraag
<u>HYU-199N</u>	DS-1280ZJ-M		Caja de conexiones para domos HYUNDAI y HiWatch™ de HIKVISION®.	Prijs op aanvraag

<u>HYU-838N</u>	HYU-838N		Junction box for HYUNDAI and HiWatch™ bullet cameras from HIKVISION®.	Prijs op aanvraag
<u>HYU-607</u>	HYU-607		Junction box for HYU-544 fisheye dome. Aluminum alloy. Side hole. 4,5 kg capacity. Waterproof	Prijs op aanvraag
<u>HYU-301N</u>	DS-1280ZJ-S		Junction box for HYUNDAI and HiWatch™ HIKVISION® bullet cameras.	Prijs op aanvraag
<u>HYU-595N</u>	DS-1272ZJ-110-TRS		Wall bracket for HYUNDAI domes.	Prijs op aanvraag
<u>HYU-252</u>	HYU-252		Connection box for HYU-250, HYU-256	Prijs op aanvraag
<u>HYU-213N</u>	DS-1273-130-TRL		Wall bracket for HYUNDAI and HiWatch™ HIKVISION® domes. Wiring holes. Aluminum.	Prijs op aanvraag
<u>HYU-358N</u>	HYU-358N		Corner bracket for HYUNDAI domes. Aluminum. 10 kg capacity	Prijs op aanvraag
<u>HYU-54</u>	HYU-54		Ceiling mount HYU-49, HYU-50, HYU-51, HYU-52, HYU-81, HYU-82	Prijs op aanvraag
<u>HYU-434</u>	DS-1294ZJ-TRL		Wall mount for HYU-484 panoramic multi sensor PTZ dome. Hardened plastic Capacity of 4.5 kg.	Prijs op aanvraag
<u>HYU-219N</u>	DS-1662		Ceiling bracket (long) for HYUNDAI and HiWatch™ HIKVISION® dome. Aluminum. Indoor/outdoor	Prijs op aanvraag

<u>HYU-603N</u>	DS-1273ZJ-140		Wall mount for HYUNDAI domes. Aluminum and steel alloy. Wiring input hole. 4,5 kg load.	Prijs op aanvraag
<u>HYU-601</u>	DS-1280ZJ-DM45		Base for HYUNDAI domes. Aluminum alloy. Side and bottom entry. 3 kg load. For indoor/outdoor	Prijs op aanvraag
<u>HYU-842</u>	DS-1272ZJ-110-TRS-BLACK		Wall mount for HYUNDAI domes. Aluminium alloy. Side and bottom entrance. Capacity of 4.5 kg. Suitable interior and exterior.	Prijs op aanvraag
<u>HYU-575</u>	DS-1227ZJ-P1		Ceiling bracket for people counting camera HYU-519	Prijs op aanvraag
<u>HYU-836</u>	DS-1280ZJ-DM21-BLACK		HYUNDAI dome base. Aluminium alloy. Side and bottom entrance. Capacity of 4.5 kg. Suitable for indoor and outdoor.	Prijs op aanvraag
<u>HYU-837</u>	DS-1280ZJ-M-BLACK		HYUNDAI dome base. Aluminium alloy. Capacity of 4.5 kg. Suitable for indoor and outdoor.	Prijs op aanvraag
<u>HYU-839</u>	DS-1280ZJ-XS-BLACK		HYUNDAI dome base. Aluminium alloy. Side and bottom entrance. Capacity of 4.5 kg.	Prijs op aanvraag
<u>HYU-545</u>	DS-1273ZJ		Junction box for HYUNDAI and HiWatch™ HIKVISION® PTZ domes	Prijs op aanvraag
<u>HYU-598</u>	DS-1273ZJ-130		Wall mount for HYUNDAI domes. Aluminium alloy. Wiring input hole. 4,5 kg load	Prijs op aanvraag
<u>HYU-56</u>	HYU-56		Support bracket HYU-49, HYU-50, HYU-51, HYU-52, HYU-81, HYU-82	Prijs op aanvraag

HYU-841	DS-1281ZJ-M-BLACK		Inclined base for HYUNDAI domes. Aluminium alloy. Side and bottom entrance. Capacity of 4.5 kg. Suitable interior and exterior.	Prijs op aanvraag
HYU-202	DS-1227ZJ		Embedded ceiling mount bracket for HYUNDAI domes. Aluminum. 4.5 kg load	Prijs op aanvraag
HYU-843	DS-1273ZJ-130-TRL-BLACK		Wall mount for HYUNDAI domes. Aluminium alloy. Side and bottom entrance. Capacity of 4.5 kg. Suitable for indoors and outdoors.	Prijs op aanvraag
HYU-599N	DS-1271ZJ-130		Ceiling mount for HYUNDAI domes. Aluminum alloy. Wiring input hole. 4,5 kg load.	Prijs op aanvraag
HYU-600	DS-1273ZJ-140-DM45		Wall mount for HYUNDAI domes. Aluminum and steel alloy. Wiring input hole. 4,5 kg load.	Prijs op aanvraag
HYU-602	DS-1271ZJ-140-DM45		Ceiling bracket for HYUNDAI domes. Aluminum alloy. Wiring input hole. 4,5 kg load.	Prijs op aanvraag
HYU-608	HYU-608		Wall mount with junction box for HYU-544 fisheye dome. Aluminum alloy. 2 kg load. 3 AXIS adjustment.	Prijs op aanvraag
HYU-546	DS-1602ZJ-BOX		Junction box for HYUNDAI and HiWatch™ HIKVISION® PTZ domes	Prijs op aanvraag
HYU-578	DS-1619ZJ		Cornice bracket for HYUNDAI PTZ domes	Prijs op aanvraag

Voorwaarden

Prijzen en specificaties
Op aanvraag

Orders

Afhankelijk van beschikbaarheid

Transport

De levertijd is 24 tot 48 uur, afhankelijk van regio's en landen en uiteraard indien niet op voorraad

Raadpleeg verzendkosten aan de verkoopafdeling

Garantie

2 jaar garantie op alle producten vanaf factuurdatum

Uitzondering zijn batterijen, harde schijven, UPS-, TFT-, LCD- en plasmamonitoren

Het dekt geen onderdelen met normale slijtage, schade als gevolg van overbelasting of storm, of oneigenlijk gebruik

Onjuiste behandeling van apparatuur leidt tot verlies van garantie

Om door te gaan met de retourzending, moet het materiaal binnen de gestelde termijn en in perfecte staat worden geretourneerd

Neem voor meer informatie en prijzen contact op met:

Ron Mantel

Securon Distributie

06 46 876 740

info@securondistributie.nl